

# DH-PHROA5.9

## Outdoor Rental LED



### Features :

- One single person can handle all the works from assembly to disassembly to maintenance.
- Magnetic panel design enables single person assembly and disassembly.
- Rear-accessible module design is ideal for fast replacement in rental & staging environment.
- Modular designed power supply and receiving card support quick maintenance.
- Climbable panel structure is designed for maintenance when hanging installation.
- Panel supports both concave and convex curve installations.



### Technical Specification

#### Model

Model	DH-PHROA5.9
-------	-------------

#### Parameters

Pixel Pitch 4.8 mm	5.9mm	
Pixel configuration	1R1G1B	
LED Type	3-in-1 Black SMD2727	3-in-1 SMD2727
Brightness	5000 cd/m <sup>2</sup>	5500 cd/m <sup>2</sup>
Color Temperature	2000K~9300K (adjustable)	
Viewing Angle	H140°, V120°	
Pixel Density	28,228 pixels/m <sup>2</sup>	
Recommended Viewing Distance	≥5.9M	
Module Size	250mm×250mm	
Cabinet Size	W500m×H500mm×D90.6mm	
Cabinet Weight	9.2 kg	
Cabinet Area	0.25 m <sup>2</sup>	
Material	Die-casting Aluminum	
Lifespan	100000 h	

Ingress Protection	IP65/IP65	
Operating Temperature/ Humidity	-20 C~+50 C/10~90%RH	
Storage Temperature/ Humidity	-30 C~+60 C/10~90%RH	
Pixels per Cabinet	84×84 pixels	
Processing Depth	16 bits	
Gray Scale	65,536 levels per color	
Color	281.4 trillion	
Service method	Rear	
Curve optional	(Outer) -3°~+10° (Inner)	
Calibration	Support luminance/chroma	
Brightness control	Manual/Automatic	
Contrast ratio	5000:1	3000:1
Video frame rate	50/60 Hz	
Rate Refresh	≥3840 Hz	
Input voltage	100-240V AC	
Input power frequency	50~60 Hz	

Input Power (max)	920 W/m <sup>2</sup>	840 W/m <sup>2</sup>
Input Power (typical)	304 W/m <sup>2</sup>	280 W/m <sup>2</sup>
LED Wavelength	R:620~630nm G:520~535nm B:465~475nm	
Driving Method	1/7 Scan, Constant Current	
Input Signal	DVI/HDMI/VGA/SDI/DP/AV/S-Video	
Rigging Form	Hanging(Max.20tiles)/Stacking(Max.20tiles)	
Data Interconnection	CAT5 Cable ( L≤100m ); multi-mode fiber ( L≤300m ); single mode fiber (L≤15km)	