

# DHI-ARC2016U-G

## General Alarm Controller



### Features

- 16 on-board zones
- 14 alarm out
- 8 alarm keypad (ARK10C)
- Two independent access control
- One group audio talk, audio announcement
- TCP/IP, 2G(-G only), PSTN



Technical Specification	
Wired Zones	16 on-board zones
Alarm Output	12 relay output (30VDC 1A), 2 strong relay output (220VAC 10A)
Network	1-ch 10M/100M Ethernet port, RJ45 port -G (GPRS 2G network)
Protocol	TCP/IP
Log	5000
Independent Security service center	2 groups phone call security center
Siren	Support
PSTN Detect	Support
Anti-cut, Anti-circuit	Support
SMS	-G Support
Remote Upgrade	Support
Audio In	1-ch 3.5mm JACK port in
Audio Out	1-ch 3.5mm JACK port out
Alternate Power	External: +12V 7AH Lead-acid battery
Power	AC 100-240V, 50/60Hz, Max 35W
Working Environment	-10°C+55°C

Overall dimensions\weight	220L*440W*44.5H mm/<3.5kg
Installation	Rack-mounted

## Ordering Information

Type	Part Number	Description
Controller	DHI-ARC2016U	General Alarm Controller
Controller	DHI-ARC2016U-G	General Alarm Controller with 2G sim card slot
Keypad	DHI-ARK10C	Alarm keypad, Max. 8pcs

## Dimensions

