

PHRIA3.91-SH

Indoor Rental LED



Features:

- The precision of die-casting aluminum cabinet splicing seam is less than 0.1mm.
- Special, adjustable locks achieve fast installation and uninstallation.
- Fanless design comes from superior heat dissipation.
- Good grey scale even at low brightness, brings profound levels and abundant colors.



Technical Specification

Model

| | |
|-------|--------------|
| Model | PHRIA3.91-SH |
|-------|--------------|

Parameters

| | |
|--|--------------|
| Pixel Pitch(mm) | 3.91 |
| Module Size (W×H) | 250×250mm |
| Module Resolution (W×H) | 64×64 |
| Pixel Type | 1R1G1B |
| LED Type | SMD2020 |
| Cabinet Size (W×H×D) | 500×500×88mm |
| Cabinet Resolution (W×H) | 128×128 |
| Cabinet Material | Aluminium |
| Cabinet Weight (kg) | 7.5 |
| Cabinet Pixel Density (Pixels/Cabinet) | 16,384 |
| Brightness (nits) | ≤800 |
| Grey Level (bit) | 13 |
| Color (trillion) | 0.55 |
| Contrast | 3000:1 |

| | |
|-------------------------------------|--------------------------------------|
| Refresh Rate (Hz) | ≥1920 |
| Driving Mode | 1/16 scan |
| Viewing Angle | 120°/120° |
| Ingress Protection (front/rear) | IP30 |
| Input Voltage | AC100~240V (+/-10%), 50/60 Hz |
| Work Temperature | -20℃~+50℃ |
| Work Humidity | 10%RH~90%RH |
| Recommended Viewing Distance (m) | ≥8.5 |
| Max Input Power (W/m ²) | 500 |
| Avg Input Power (W/m ²) | 200 |
| Signal Interface (compatible) | VGA,DVI,HDMI |
| Communication Connection | CAT5E:<100m, Single mode fiber:<10km |
| Maintenance Mode | Rear maintenance |
| Cabinet Fast Lock | Taperlock |
| Max Number of Hoisting Installation | 15 |