

# PHRIA4.81-SS-L

Indoor Rental LED



## Features:

- Ultra thin cabinet makes it easy to carry and assemble.
- Save much time during events for multi-installation ways.
- ±15 degree viewing angle can be adjusted to meet curve and even round design.



## Technical Specification

### Model

Model	PHRIA4.81-SS-L
-------	----------------

### Parameters

Pixel Pitch(mm)	4.81	
Module Size (W×H)	250×250mm	
Module Resolution (W×H)	52×52	
Pixel Type	1R1G1B	
LED Type	SMD1921	SMD2020
Cabinet Size (W×H×D)	500×1000×72mm	500×1000×70mm
Cabinet Resolution (W×H)	104×208	
Cabinet Material	Aluminium	
Cabinet Weight (kg)	15	14
Cabinet Pixel Density (Pixels/Cabinet)	21,632	
Brightness (nits)	≤800	
Grey Level (bit)	13	
Color (trillion)	0.55	
Contrast	3000:1	

Refresh Rate (Hz)	≥1920	≥1200
Driving Mode	1/13 scan	
Viewing Angle	140°/140°	120°/120°
Ingress Protection (front/rear)	IP30	
Input Voltage	AC100~240V (+/-10%), 50/60 Hz	
Work Temperature	-20℃~+50℃	
Work Humidity	10%RH~90%RH	
Recommended Viewing Distance (m)	≥10	
Max Input Power (W/m <sup>2</sup> )	572	
Avg Input Power (W/m <sup>2</sup> )	230	440
Signal Interface (compatible)	VGA,DVI,HDMI	176
Communication Connection	CAT5E:<100m, Single mode fiber:<10km	
Maintenance Mode	Rear maintenance	
Cabinet Fast Lock	Spring lock	
Max Number of Hoisting Installation	10	