

PHRIA4.81-SS

Indoor Rental LED



Features:

- Only 7.5kg for each cabinet, save more convenient installation and cheaper shipping cost.
- Each cabinet thickness is 80mm, with beautiful die-cast aluminum frame design.
- Cabinet dimensional tolerance can be controlled within 0.1mm.
- There are handlers on top and sides of cabinet, and it is more convenient to assemble and do maintenance for screen.



Technical Specification

Model

Model	PHRIA4.81-SS
-------	--------------

Parameters

Pixel Pitch(mm)	4.81
Module Size (W×H)	250×250mm
Module Resolution (W×H)	52×52
Pixel Type	1R1G1B
LED Type	SMD1921
Cabinet Size (W×H×D)	500×500×80mm
Cabinet Resolution (W×H)	104×104
Cabinet Material	Aluminium
Cabinet Weight (kg)	7.5
Cabinet Pixel Density (Pixels/Cabinet)	21,632
Brightness (nits)	≤800
Grey Level (bit)	13
Color (trillion)	0.55
Contrast	3000:1

Refresh Rate (Hz)	≥1920
Driving Mode	1/13 scan
Viewing Angle	140°/140°
Ingress Protection (front/rear)	IP30
Input Voltage	AC100~240V (+/-10%), 50/60 Hz
Work Temperature	-20℃~+50℃
Work Humidity	10%RH~90%RH
Recommended Viewing Distance (m)	≥10
Max Input Power (W/m ²)	592
Avg Input Power (W/m ²)	240
Signal Interface (compatible)	VGA,DVI,HDMI
Communication Connection	CAT5E:<100m, Single mode fiber:<10km
Maintenance Mode	Rear maintenance
Cabinet Fast Lock	Handle lock
Max Number of Hoisting Installation	15