

# PHRIA5.68-SS-L

Indoor Rental LED



## Features:

- Ultra thin cabinet makes it easy to carry and assemble.
- Save much time during events for multi-installation ways.
- $\pm 15$  degree viewing angle can be adjusted to meet curve and even round design.



## Technical Specification

### Model

Model	PHRIA5.68-SS-L
-------	----------------

### Parameters

Pixel Pitch(mm)	5.68
Module Size (W×H)	250×250mm
Module Resolution (W×H)	44×44
Pixel Type	1R1G1B
LED Type	SMD3528
Cabinet Size (W×H×D)	500×1000×72mm
Cabinet Resolution (W×H)	88×176
Cabinet Material	Aluminium
Cabinet Weight (kg)	15
Cabinet Pixel Density (Pixels/Cabinet)	15,488
Brightness (nits)	≤800
Grey Level (bit)	13
Color (trillion)	0.55
Contrast	1500:1

Refresh Rate (Hz)	≥1200
Driving Mode	1/11 scan
Viewing Angle	120°/120°
Ingress Protection (front/rear)	IP30
Input Voltage	AC100~240V (+/-10%), 50/60 Hz
Work Temperature	-20℃~+50℃
Work Humidity	10%RH~90%RH
Recommended Viewing Distance (m)	≥12
Max Input Power (W/m <sup>2</sup> )	548
Avg Input Power (W/m <sup>2</sup> )	220
Signal Interface (compatible)	VGA,DVI,HDMI
Communication Connection	CAT5E:<100m, Single mode fiber:<10km
Maintenance Mode	Rear maintenance
Cabinet Fast Lock	Spring lock
Max Number of Hoisting Installation	10