

PHRIA6.25-SS-L

Indoor Rental LED



Features:

- Ultra thin cabinet makes it easy to carry and assemble.
- Save much time during events for multi-installation ways.
- ± 15 degree viewing angle can be adjusted to meet curve and even round design.



Technical Specification

Model

Model	PHRIA6.25-SS-L
-------	----------------

Parameters

Pixel Pitch(mm)	6.25
Module Size (W×H)	250×250mm
Module Resolution (W×H)	40×40
Pixel Type	1R1G1B
LED Type	SMD3528
Cabinet Size (W×H×D)	500×1000×70mm
Cabinet Resolution (W×H)	80×160
Cabinet Material	Aluminium
Cabinet Weight (kg)	15
Cabinet Pixel Density (Pixels/Cabinet)	12,800
Brightness (nits)	≤800
Grey Level (bit)	13
Color (trillion)	0.55
Contrast	1500:1

Refresh Rate (Hz)	≥1200
Driving Mode	1/10 scan
Viewing Angle	120°/120°
Ingress Protection (front/rear)	IP30
Input Voltage	AC100~240V (+/-10%), 50/60 Hz
Work Temperature	-20℃~+50℃
Work Humidity	10%RH~90%RH
Recommended Viewing Distance (m)	≥13
Max Input Power (W/m ²)	508
Avg Input Power (W/m ²)	204
Signal Interface (compatible)	VGA,DVI,HDMI
Communication Connection	CAT5E:<100m, Single mode fiber:<10km
Maintenance Mode	Rear maintenance
Cabinet Fast Lock	Spring lock
Max Number of Hoisting Installation	10