

PHVOA9-SH

Outdoor Stadium LED



Features:

- Meet a variety of high protection demand: waterproof, sunscreen, anti-impact.
- High refresh, high gray scale, high contrast, good consistency, high quality fine picture effect
- Adjustable screen angle to ensure the best view of the audience
- Unique soft mask and soft protective pad to ensure security personnel safety



Technical Specification

Model

Model	PHVOA9-SH
-------	-----------

Parameters

Pixel Pitch(mm)	9.375
Module Size (W×H)	1250×75mm
Module Resolution (W×H)	128×8
Pixel Type	1R1G1B
LED Type	SMD3535
Cabinet Size (W×H×D)	1200×900×140mm
Cabinet Resolution (W×H)	128×96
Cabinet Material	Aluminum
Cabinet Weight (kg)	45
Pixel Density (Pixels/Cabinet)	12,288
Brightness (nits)	5500
Grey Level (bit)	15
Color (trillion)	35.18
Contrast	1500:1

Refresh Rate (Hz)	≥9060
Driving Mode	1/2 scan
Viewing Angle	140°/140°
Ingress Protection (front/rear)	IP65/IP54
Input Voltage	AC100~240V (+/-10%), 50/60 Hz
Work Temperature	-20℃~+50℃
Work Humidity	10%RH~90%RH
Recommended Viewing Distance (m)	≥20
Max Input Power (W/m ²)	450
Avg Input Power (W/m ²)	180
Signal Interface (compatible)	AV,S-Video,VGA,DVI,HDMI,SDI,DP
Communication Connection	CAT5E:<100m, Single mode fiber:<10km
Maintenance Mode	Rear Maintenance