

DHI-ARD812

Panic Button



- Surface mount with screws.
- Works in a wide range of environments with a voltage that is no more than 250 VDC and a current that is no more than 300 mA.
- Works without a power supply.
- A reset key is included to quickly reset the device if necessary.

System Overview

The device triggers alarms with the press of a button.

Scene

Ideal for locations where alarms need to be manually triggered in emergencies, such as bank counters, accessible toilets and rooms for the elderly.

Technical Specification

Port

Alarm Output 1, NC/NO, 250 VDC, Max. 300 mA

General

Operating Temperature	-10 °C to +55 °C (+14 °F to +131 °F)
Operating Humidity	≤95% (RH)
Product Dimensions	49.5 mm × 32.5 mm × 53.5 mm (1.95" × 1.28" × 2.11") (L × W × H)
Net Weight	34 g (0.07 lb)
Gross Weight	41.5 g (0.09 lb)
Installation	Surface mount
Casing Material	ABS
Appearance Color	Cineros
Certifications	CE
Anti-corrosion Level	Basic Protection
Storage Temperature	-10 °C to +55 °C (+14 °F to +131 °F)
Storage Humidity	≤95% (RH)
Packaging Dimensions	56.0 mm × 35.0 mm × 56.0 mm (2.20" × 1.38" × 2.20") (L × W × H)

Ordering Information

Type	Model	Description
Panic Button	DHI-ARD812	Panic Button

Dimensions (mm[inch])

