

# DHI-ASR2200A-B

Dahua Card Swiping, Bluetooth card Reader



#### Scene

Suitable for a variety of scenes including office buildings, schools, factories, residential areas, the financial sector, insurance industry, government departments, maritime safety bureaus and CBD business centers.

Technical Specification		
Basic		
Product Type	Card reader	
Buzzer	Yes	
Casing Material	Tempered glass/PC	
Function		
Unlock Mode	Card swiping/Bluetooth	
Card Type	IC card	
Bluetooth	Yes	
Performance		
Response Time	0.1 s	
Card Reading Distance	0 cm–5 cm (0"–1.97")	
Bluetooth Distance	<ol> <li>Short-range: ≤0.2 m (0.66 ft).</li> <li>Mid-range: ≤2 m (6.56 ft).</li> <li>Long-range: ≤10 m (32.81 ft).</li> <li>The Bluetooth unlock range might differ depending on models of your phone and the environment.</li> </ol>	
Port		
RS-485	1	
Wiegand	1 output channel	
Alarm		
Tamper Alarm	Yes	


- PC material, tempered glass panel and IP66, suitable for indoor and outdoor use.
- Contactless card reading for IC cards (Mifare cards).
- Unlock through card swiping and Bluetooth.
- Communicates through the RS-485 port, Wiegand port, and Bluetooth.
- Prompts using the buzzer and indicator light.
- Supports the anti-tampering alarm.
- The built-in watchdog program can detect and control the abnormal operation status of the equipment and perform recovery processing to ensure the long-term operation of the equipment.
- · All the connection ports have overcurrent and overvoltage protection.
- · Works with the DMSS mobile client.

Power Supply	12 VDC, 0.5 A
Protection	IP66
Power Consumption	Standby ≤0.9 W, working ≤1.7W
Product Dimensions	135 mm × 40 mm × 15 mm (5.31" × 1.57" × 0.59") (H × W × D)
Packaging Dimensions	195 mm × 75 mm × 52 mm (7.68" × 2.95" × 2.05") (H × W × D, 1 in inner carton) 415 mm × 400 mm × 230 mm (16.34" × 15.75" × 9.06") (H × W × D, carton)
Operating Temperature	-30 °C to +70 °C (-22 °F to +158 °F)
Operating Humidity	5%–95% (RH), non-condensing
Operating Environment	Outdoor
Gross Weight	0.16 kg (0.35 lb)
Installation	Surface Mount
Certifications	CE; FCC

Ordering Information		
Туре	Model	Description
Access Reader	DHI-ASR2200A-B	Dahua Card Swiping, Bluetooth card Reader


# DHI-ASGB8XXH-X


### Installation



## Dimensions (mm[inch])







Rev 002.000 © 2023 Dahua. All rights reserved. Design and specifications are subject to change without notice. The images, specifications and information mentioned in the document are only for reference, and might differ from the actual product.