

DHI-ASR2201A

Access Reader



Series Overview

As a key part of the access control system, the DHI-ASR2201A access control card reader supports card and password unlock, and sends the information to the access controller for verification. With a thin and elegant design, it is applicable to industrial zones, office buildings, schools, factories, stadiums, CBD, residential area, government properties, etc.

Technical Specification

Basic	
Product Type	Slim Card Reader
Buzzer	Yes
Casing	Tempered glass/PC
Function	
Unlock Mode	Card swiping/password Multiple unlocking modes
Card Type	IC card
Performance	
Response Time	0.1 s
Card Reading Distance	0 cm–5 cm (0"–1.97")
Port	
RS-485	1 channel
Wiegand	1 output channel
Alarm	
Tamper Alarm	Yes
General	
RS-485	1 channel

- PC material, tempered glass panel and IP66, suitable for indoor and outdoor use.
- Support contacless recognition of IC card (Mifare card).
- Support card unlock.
- Support communication through RS-485 and Wiegand 34 (Wiegand 26 can be configured).
- Support buzzer and indicator prompt.
- Support anti-tampering alarm.
- The built-in watchdog can detect and control the abnormal operation status of the equipment and perform recovery processing to ensure the long-term operation of the equipment.
- All connection ports have overcurrent and overvoltage protection.



Power Supply	12V 0.5A DC
Protection	IP66 (silicon sealant is needed, see the manual)
Power Consumption	Standby ≤ 0.9W, working ≤ 1.7W
Product Dimensions	135 mm × 40 mm × 15 mm (5.31" × 1.57" × 0.59") (L × W× H)
Packaging Dimensions	195 mm × 75 mm × 52 mm (7.68" × 2.95 × 2.05") (L × W× H, 1 in inner carton) 415 mm × 400 mm × 230 mm (16.34" × 15.75" × 9.06") (L × W × H, carton)
Operating Temperature	-30°C to +70°C (-22°F to +158°F)
Operating Humidity	5%RH–95% (non-condensing)
Operating Environment	Indoor; outdoor
Gross Weight	0.16 kg (0.35 lb)
Installation	Surface mount
Certifications	CE; FCC

ASR2 Series | DHI-ASR2201A

Application **Ordering Information** Model Туре Description DHI-ASR2201A Outdoor Waterproof Access DHI-ASR2201A Password IC Card Reader Slim Model Reader (777T) Management Platform Client Switch :::: 🕂 Dimensions (mm[inch]) [0.65] 5.0 [0.59] Access Controller <u>9.5 [0.3</u> 14.0 [0.5

Lock

Exit Button

Card Reader

Alarm Light

Rev 002.000 © 2023 Dahua. All rights reserved. Design and specifications are subject to change without notice. The images, specifications and information mentioned in the document are only for reference, and might differ from the actual product.

www.dahuasecurity.com