

DH-PFB5203C

In-ceiling Mount Bracket



- \cdot The screws are embedded in the frame and the camera neatly installs into its bracket without hindering its visual range.
- · Easy to disassemble and maintain.
- · Easy to install and aesthetically pleasing.
- · The bracket is stable, as it firmly secures the camera in position on the ceiling.





System Overview

Dahua Mounting Bracket works with front-end services, supporting installation methods such as wall mount, pole mount, corner mount and in-ceiling mount. Select brackets are designed to suit complex scenes, making them convenient to use in environments with high temperatures, humidity, frequent vibrations, and in locations that are highly corrosive. These highly reliable brackets are easy to install and use.

Scene

Ideal for mounting cameras, and works in temperatures ranging from $-40\,^{\circ}\text{C}$ to $+60\,^{\circ}\text{C}$ ($-40\,^{\circ}\text{F}$ to $+140\,^{\circ}\text{F}$) and in environments with a relative humidity of less than 90%.

Storage Temperature	-40 °C to +60 °C (-40 °F to +140 °F)
Storage Humidity	10%-90% (RH)
Anti-corrosion Level	Basic Protection

Ordering Information		
Туре	Model	Description
Camera DH-PFB5203C Mount PFB5203C	DH-PFB5203C	In-ceiling Mount Bracket
	PFB5203C	In-ceiling Mount Bracket

Technical Specification


Structure

Casing Material	SPCC; PC
Product Dimensions	Φ172.7 mm × 73.2 mm (Φ6.80" × 2.88")
Appearance Color	White
Net Weight	0.31 kg (0.68 lb)
Gross Weight	0.46 kg (1.01 lb)
Load Bearing	1.0 kg (2.20 lb)
Installation	In-ceiling mount
Applicable Model	Please see "Camera Accessories Selection"
Packaging Dimensions	212.0 mm × 212.0 mm × 106.0 mm (8.35" × 8.35" × 4.17") (L × W × H)


Environment

Operating Temperature	-40 °C to +60 °C (-40 °F to +140 °F)
Operating Humidity	<90% (RH)

Installation



Dimensions (mm[inch])



Package Information

- \cdot In-ceiling mount bracket \times 1
- M4×14 screw × 3
- S3.0 wrench \times 1
- Installation Guide × 1