

DH-PFM301-US

DC12V2A Power Adapter



- Designed with an indicator light that displays its working status.
- Wall mount installation.
- Shell flame resistance V-0 level.

Technical Specification

Function

Input Voltage	180–264 VAC
Output Voltage	12 VDC
Rated Output Current	2 A
Rated Power	24 W
Power Consumption In Idle	≤0.3 W
Efficiency	≥82.09%

Port

Input Port	North American Standard power cord
Output Plug	Φ5.5 mm × Φ2.1 mm × 11.0 mm (0.22" × 0.08" × 0.43") (OD × ID × L)

Protection

Protection	Protects against overcurrent, overvoltage, overheating and short circuits.
Surge Protection Grade	Common mode: ±4 kV Differentiate mode: ±2 kV
Statics Protection	Air discharge: ±8 kV Contact discharge: ±4 kV

Structure

Installation	Wall mount
Product Dimensions	88.0 mm × 74.5 mm × 35.0 mm (3.46" × 2.93" × 1.38")
Appearance Color	Gray
Net Weight	0.14 kg (0.31 lb)
Gross Weight	0.17 kg (0.37 lb)
Packaging Dimensions	131.5 mm × 76.5 mm × 35.5 mm (5.18" × 3.01" × 1.40")
Output Cable Length	800 mm (31.50")

Environment

Operating Temperature	−30 °C to +40 °C (−22 °F to +104 °F)
Operating Humidity	10%–90% (RH)
Storage Temperature	−30 °C to +85 °C (−22 °F to +185 °F)
Storage Humidity	10%–90% (RH)

Ordering Information

Type	Model	Description
Power Adapter	DH-PFM301-US	Power Adapter

Dimensions (mm[inch])

