

DH-PFM371-M180

180W Monocrystalline Silicon Solar Module



Technical Specification

Protection

Hoteedon	
Туре	Monocrystalline silicon
Max. Power	180W
Output Voltage	32.66 V
Operating Current	5.51 A
Short Circuit Current	6.0 A
Open Circuit Voltae	39.63 V
Conversion Rate of Solar Panel Components	18.34%
Light Conversion Rate of Silicon Chips	≥22%
Max. Mechanical Load	Front side: 5400 Pa Rear side: 2400 Pa
Dielectric Strength	1000 V
Protection	IK07
Power-to-temperature Coefficient	-0.42%/K
Current-to-temperature Coefficient	0.04%/K
Voltage-to-temperature Coefficient	-0.3%/K
Main Body Material	Silicon; tempered glass; aluminium frame
Silicon Chip Size	70 mm × 210 mm (2.76" × 8.27") (L × W)
Silicon Chip Array	4 ×15
Port	
Output Port	Compatible MC4 connector

- \cdot Effectively saves energy, consuming no more than 180 W.
- Absorbs light and converts the energy of light into electricity in a balanced way using multiple busbar solar cells.
- Desgined with high-quality glass and an etching treatment on the surface of the cells, the device remains stable in different environment.
- Built to be durable, the device can withstand extreme conditions such as places that are in high altidues, or that have high salt density and low temperatures.
- \cdot Long lifespan of up to 25 years.

General	
Product Dimensions	1115 mm × 880 mm × 35 mm (43.90" × 34.65" × 1.38") (L × W × H)
Packaging Dimensions	1164 mm × 929 mm × 148 mm (45.83" × 36.57" × 5.83") (L × W × H)
Packaging Method	2 pieces in each carton
Net Weight	9.5 kg (20.94 lb)
Gross Weight	38 kg (83.78 lb)
Environment	
Operating Altitude	<3000 m (9842.52 ft)
Applicable Area	Locations with exposure to solar radiation for more than 3.5 hours per day
Operating Temperature	-40 °C to +85 °C (-40 °F to +185 °F)
Operating Humidity	< 95% (RH)
Storage Temperature	0 °C to +40 °C (+32 °F to +104 °F)
Storage Humidity	< 95% (RH)
Certifications	
Certifications	CE: EN 61000-6-1,EN 61000-6-3 UKCA: EN 61000-6-1,EN 61000-6-3 FCC: 47 CFR Part 15,Subpart B

Solar Series | DH-PFM371-M180

Ordering Information

Model


Туре

Solar Series DH-PFM371-M180

180W Monocrystalline Silicon Solar Module

Description

Dimensions (mm[inch])



Rev 002.000 © 2022 Dahua. All rights reserved. Design and specifications are subject to change without notice. The images, specifications and information mentioned in the document are only for reference, and might differ from the actual product.