

DH-PFM376-G 275W Solar Mount



- · Q235 carbon structural steel with hot-dip galvanization and anti-corrosion protection.
- Adjusts to multiple inclination angles, such as 10°, 20°, 30°, 40° and 50°, making it suitable for use in different latitudes.
- \cdot Pole mount: supports being mounted to poles that are 150 to 220 mm in diameter.
- \cdot Supports carrying up to 2 solar panels, and is only suitable for use with DH-PFM371-M275 solar panels.


reennear opeennearion		
General		

Technical Specification


Pole mount
Q235
Sliver Gray
150 mm-220 mm
10°; 20°; 30°; 40°; 50°
2 pcs × 275 W solar panels
38 kg (83.78 lb)
40 kg (88.18 lb)
1730.7 mm × 1810.0 mm × 909.2 mm (68.14" × 71.26" × 35.80")
1930 mm × 290 mm × 165 mm (75.98" × 71.26" × 6.49")
-40 °C to +85 °C (-40 °F to 185 °F)
< 95% (RH)
-20 °C to +60 °C (-4 °F to 140 °F)
< 95% (RH)

Ordering Information Type Model Description Solar Series DH-PFM376-G 275W Solar Mount

Dimensions (mm[inch])









Applicatinon



Rev 002.000 © 2022 Dahua. All rights reserved. Design and specifications are subject to change without notice. The images, specifications and information mentioned in the document are only for reference, and might differ from the actual product.