


# DH-PFS3008-8ET

Unmanaged Desktop Switch



- Plug and play: No configuration required
- Robust design: 24/7 stable performance in operating temperature from 0°C to 40°C
- Optimized performance: Provides full-speed transmission in all ports simultaneously
- Flexible deployment: Supports desktop and wall mount



## Functions

### Full Fast Ethernet Ports

Equipped with 8 10/100 Mbps ports enable fast transmission for your network, ideal for home and small office scenario.

### Silent Operation

Designed with durable metal casing and fanless structure, ensure the heat dissipation during a noiseless operation.

### Easy Installation

Both deployment and settings are designed to make a hassle-free experience for our customers, while providing an optimal operation.

## Scene



Home



Shop



Dormitory



Meeting Room

Technical Specification

Performance	
Layer	Layer 2
Hardware	
Standard Power Supply	Yes
Ethernet Port	8
Ethernet Port Rate	1000 Mbps
Power Supply	5V/600mA DC
Operating Temperature	−10°C to +55°C (+14°F to +131°F)
Operating Humidity	10%–90% (RH)
Storage Temperature	−20°C to +70°C (−4°F to +158°F)
Storage Humidity	10%–90% (RH)
Power Consumption	< 3W

Performance	
Switching Capacity	1.6 Gbps
Packet Forwarding Rate	1.1904 Mpps
Packet Buffer Memory	768 Kbit
MAC Table Size	2K
Standards Compliance	IEEE 802.3; IEEE 802.3u; IEEE 802.3x; IEEE802.3az

General	
ESD	Air discharge: 8kV Contact discharge: 6kV
Thunderproof	Common mode: 2kV
Net Weight	210 g (0.46 lb)
Dimensions	150 mm × 70 mm × 22.6 mm (5.91" × 2.76" × 0.89") (L × W × H)

Dimensions (mm[inch])

