

DHI-LDH43-SAI400K

Dahua 43 inch Wall-mounted LCD Digital Signage



Series Overview

Simple and elegant, the LCD Digital Signage is built of metal and has an industrial-grade design. With its A-level LCD panel, it has a long lifespan and displays high quality visuals. It can access the network, support audio and videos, release multimedia information, and broadcast advertisements.

Functions

Rich Media

A wide variety of media can be inserted into your projects such as images, videos, audio and files in Word, Excel, PPT, TXT or PDF format. It also supports insertion of webpages, streaming media, scrolling subtitles, notifications and more.

Program Plug-ins

Multiple elements can be incorporated into your projects, such as the weather, time and countdown timer, to suit your needs.

Local Release

Media can be conveniently imported to the digital signage through a USB flash drive to create and release projects.

Release through the Network

Projects can be easily created on the Media Publishing System (MPS) platform when the device is connected to the network, and then directly sent to the terminal device to be played.

Play Plans

The system simplifies broadcasting with general and cut-in plans. General plans, once activated, control how media is played on terminal devices. Cut-in plans can be directly released without approval.

- Designed with an industrial-grade panel. It works up to 16 hours a day.
- Includes a mainstream quad-core CPU, Android system, and decodes up to 4K resolution.
- Plays and releases programs in multiple modes.
- With intelligent split screen, its page layout can be freely adjusted, making it suitable for a variety of scenes.
- Designed with B/S architecture, the device manages programs by time and location, and generates operation reports.
- Supports encrypting platform data transmission, multi-level permission review for program release and terminal password protection.
- The device offers unified platform management, and can be remotely controlled by the platform.

Play Modes

The two play modes, carousel and temporary plan, add variety to the presentation of your projects. Carousel mode plays multiple media in a loop, with no need for manual configuration. Temporary plan mode fills in to play your media when there are no general plans and cut-in plans. It can be played with scrolling subtitles.

Custom Play Time

The play schedules are highly flexible. General plans can be scheduled to play weekly or you can personalize your own time schedule for them. Cut-in plans can be tailored by period, duration, and the number of play times.

Scrolling Subtitles

Subtitles can be set to scroll smoothly across the screen, displaying your desired content.

Split Screen

The screen can be divided into multiple windows, with each one showcasing different content.

Scene

Ideal for communities, malls, supermarkets, hotels, enterprises, the government and various industries such as the advertising, catering, entertainment, tourism, culture, sports, education, finance, and healthcare industries.

SAI Series | DHI-LDH43-SAI400K

Technical Specification		General		
LCD Panel		Power Supply	100–240 VAC, 50/60 Hz	
Panel Dimensions	43 inch	Power Consumption	≤140 W	
Backlight	DLED	Standby Power Consumption	≤ 0.5 W	
LCD Technology	IPS/VA	Operating Temperature	0 °C to +40 °C (+32 °F to +104 °F) (avoid direct sunlight)	
Aspect Ratio	16:9	Storage Temperature	–20 °C to +60 °C (–4 °F to +140 °F)	
Brightness	500 cd/m²(typ.)	Operating Humidity	10%-85% (RH), non-condensing	
Contrast	IPS 1200:1(typ.) / VA 4000:1(typ.)	Storage Humidity	10%–90% (RH), non-condensing	
Display Colors	10 bit (8 bit + FRC), 1.07B colors	Product Material	Metal casing	
Resolution	3840 (H) × 2160 (V)	Casing Color (Frame/Rear)	Black	
Viewing Angle	178° (H); 178° (V)		956 mm × 546 mm × 57.9 mm (37.64" × 21.50" × 2.28")	
Response Time	8 ms(typ.)	Product Dimensions	(without bracket)	
Surface Treatment	Haze 1%	Packaging Dimensions	1085 mm × 150 mm × 693 mm (42.72" × 5.91" × 27.28")	
Built-in System		Net Weight	10 kg (22.05 lb)	
Operating System	Android 8.1	Gross Weight	15 kg (33.07 lb)	
CPU	4 cores A17, 1.6 GHZ	Installation	Wall mount	
RAM	2 GB	Display Mode	Landscape	
ROM	16 GB	Display Wode	Wall-mount bracket, power cord, legal and regulatory	
Video Decoding	2-ch H.264 1080p@25 fps; 4-ch H.265 1080p@25 fps; 4-ch H.265 1080p@30 fps; 2-ch H.264 1080p@25 fps; 2-ch H.265 1080p@30 fps; 2-ch H.264 4K@25 fps; 2-ch H.265 4K@30 fps; 1-ch H.265 4K@60 fps; The decoding capacity statistics are based on tests with a single video file.	Accessory Certification Certifications		abel, user's manual, remote control
Function		Ordering Information	ı	
Audio Compression	MPEG-3, WMA, WAV	Туре	Model	Description
Video Compression	MPEG-4, H.264/AVC, H.265/HEVC	LCD Digital Signage	DHI-LDH43-SAI400K	Dahua 43 inch Wall-mounted LCD Digital Signage
Video Format	mp4, avi, mov, asf, mkv, wmv			
Device Ports		Dimensions (mm[inch])		
Network Port	1 × RJ–45 10/100/1000 Mbps self-adaptive Ethernet port			
Wi-Fi	No (Can be customized)			
Bluetooth	NO			with bracket)
Data Transmission Ports	1 × TF card slot, up to 128 GB 2 × USB 2.0 ports (type A)			460.0 [18.11]
Video Input	1 × HDMI 1.4 (1080p @60Hz)			
Video Output	No			
Audio Port	1 × 3.5 mm jack Mic			
IR Receiver	Yes		, <u>, , , , , , , , , , , , , , , , , , </u>	

Ø 6.0 (Ø 0.24)

Rev 002.000 © 2024 Dahua. All rights reserved. Design and specificatons are subject to change without notce Pictures in the document are for reference only, and the actual product shall prevail.

2×5W

Speaker

Built-in Speaker