

DHI-LDH65-WAI200K

Dahua 65 inch LCD Digital Signage



- Designed with an industrial-grade panel. It works up to 24 hours a day.
- Includes a mainstream quad-core CPU and Android system.
- Plays and releases programs in multiple modes.
- With intelligent split screen, its page layout can be freely adjusted, making it suitable for a variety of scenes.
- Designed with B/S architecture, the device manages programs by time and location, and generates operation reports.
- Supports encrypting platform data transmission, multi-level permission review for program release and terminal password protection.
- The device offers unified platform management, and can be remotely controlled by the platform.

Series Overview

Simple and elegant, the LCD Digital Signage is built of metal and has an industrial-grade design. With its A-level LCD panel, it has a long lifespan and displays high quality visuals. It can access the network, support audio and videos, release multimedia information, and broadcast advertisements.

Functions

Rich Media

A wide variety of media can be inserted into your projects such as images, videos, audio and files in Word, Excel, PPT, TXT or PDF format. It also supports insertion of webpages, streaming media, scrolling subtitles, notifications and more.

Program Plug-ins

Multiple elements can be incorporated into your projects, such as the weather, time and countdown timer, to suit your needs.

Local Release

Media can be conveniently imported to the digital signage through a USB flash drive to create and release projects.

Release through the Network

Projects can be easily created on the Media Publishing System (MPS) platform when the device is connected to the network, and then directly sent to the terminal device to be played.

Play Plans

The system simplifies broadcasting with general and cut-in plans. General plans, once activated, control how media is played on terminal devices. Cut-in plans can be directly released without approval.

Play Modes

The two play modes, carousel and temporary plan, add variety to the presentation of your projects. Carousel mode plays multiple media in a loop, with no need for manual configuration. Temporary plan mode fills in to play your media when there are no general plans and cut-in plans. It can be played with scrolling subtitles.

Custom Play Time

The play schedules are highly flexible. General plans can be scheduled to play weekly or you can personalize your own time schedule for them. Cut-in plans can be tailored by period, duration, and the number of play times.

Scrolling Subtitles

Subtitles can be set to scroll smoothly across the screen, displaying your desired content.

Split Screen

The screen can be divided into multiple windows, with each one showcasing different content.

Remote Management

From the comfort of the platform, you can remotely power on and off the device, restart it, turn its display on and off, rotate its screen, and adjust its brightness and volume.

Scene

Ideal for communities, malls, supermarkets, hotels, enterprises, the government and various industries such as the advertising, catering, entertainment, tourism, culture, sports, education, finance, and healthcare industries.

WAI Series | DHI-LDH65-WAI200K


| Technical Specification | | | General | |
|-------------------------|--|--------------------|------------------------------|--|
| LCD Panel | | | Power Supply | 180-264V, 50/60Hz |
| Panel Dimensions | 65 inch | | Power Consumption | ≤460 W |
| Backlight | DLED | | Standby Power Consumption | ≤15 W with fans |
| LCD Technology | IPS | | Operating Temperature | 0 °C to +40 °C (+32 °F to +104 °F) |
| Aspect Ratio | 9: 16 | | Storage Temperature | -10 °C to +60 °C (14 °F to +140 °F) |
| Brightness | 3000 cd/m ² (typ.) | | Operating Humidity | 10%–85% (RH), non-condensing |
| Contrast | 1200: 1 (typ.) | | Storage Humidity | 10%–90% (RH) |
| Display Colors | 8 bit, 16.7M colors | | Product Material | Metal casing |
| Resolution | 1080 (H) × 1920 (V) | | Casing Color (Frame/Rear) | Black |
| Viewing Angle | 178° (H); 178° (V) | | | |
| Response Time | 8 ms (typ.) | Product Dimensions | | 843.6 mm × 1468.6 mm × 85.5 mm |
| Surface Treatment | Haze 25% | | Packaging Dimensions | 1620 mm x 266 mm x 1075 mm |
| Built-in System | | | Net Weight | 62kg |
| Operating System | Android 8.1 | | Gross Weight | 73kg |
| CPU | 4 cores A17, 1.6 GHZ | | Installation | Ceiling mount/Wall mount |
| RAM | 2 GB | | Display Mode | Portrait |
| ROM | 16 GB | | Wall Mount VESA | 400 mm × 400mm |
| Video Decoding | 2-ch H.264 1080p@25 fps; 4-ch H.265 1080p@25 fps; 4-ch H.265 1080p@30 fps; 2-ch H.264 1080p@25 fps; 2-ch H.265 1080p@30 fps; The decoding capacity statistics are based on tests with a single video file. | | Accessory | Ceiling mount bracket, power cord, legal and regulatory information, remote control, screw |


Function

| Audio Compression | MPEG-3, WMA, WAV | | | | |
|-------------------------|--|--|--|--|--|
| Video Compression | MPEG-4, H.264/AVC, H.265/HEVC | | | | |
| Video Format | mp4, avi, mov, asf, mkv, wmv | | | | |
| Device Ports | | | | | |
| Network Port | $1\times \text{RJ}45$ 10/100/1000 Mbps self-adaptive Ethernet port | | | | |
| Wi-Fi | Optional (External Wi-Fi module) | | | | |
| Bluetooth | NO | | | | |
| Data Transmission Ports | 1 × TF card slot, up to 128 GB 2 × USB 2.0 ports (type A) | | | | |
| Video Input | 1 × HDMI 1.4 (1080p @60Hz) | | | | |
| Video Output | NO | | | | |
| Audio Port | 1 × 3.5 mm jack Mic | | | | |
| IR Receiver | Yes | | | | |
| Speaker | | | | | |
| Built-in Speaker | 2 × 5 W | | | | |

| Ordering Information | | | | | | |
|----------------------|-------------------|--------------------------------------|--|--|--|--|
| Туре | Model | Description | | | | |
| LCD Digital Signage | DHI-LDH65-WAI200K | Dahua 65 inch LCD Digital Signage | | | | |

Dimensions (mm[inch])





© 2023 Dahua. All rights reserved. Design and specifications are subject to change without notice. The images, specifications and information mentioned in the document are only for reference, and might differ from the actual product. Rev 002.000