

# DHL55

## 55" FHD LCD Monitor



### Features:

- Industrial level LCD panel, suitable for continuous 24/7 operation
- Built-in 3D COMB filter and 3D noise reduction
- 8ms fast response time for no motion blur, judder or ghosting
- High fidelity digital processing for a brilliant and vivid video
- Brightness smart detection, power-saving
- Using tamper-proof metal housing
- Professional thermal design to extend equipment lifespan
- Wide array of connectivity options HDMI, DVI, VGA, BNC, support video loop



### Technical Specification

#### Model

Model	DHL55
-------	-------

#### Display

Screen Size	54.6"
Aspect Ratio	16:9
Resolution	1920×1080 (FHD)
Backlight	LED
Brightness/Luminance	500 cd/ m <sup>2</sup>
Contrast	1200:1
Display Color	16.7M(8bit)
Viewing Angle(H/V)	178°(H)/178°(V)
Response Time	8ms
Refresh Rate	60Hz

#### Signals

Input	CVBS(BNC)×2, VGA(D-Sub)×1, DVI-D×1, HDMI×1, Audio×1, RJ45(RS232)×1, USB×1	
Output	CVBS(BNC)×2, RS232×1	
	Speaker	10W×2

#### General

Power Supply	AC100~240V (+/-10%), 50/60 Hz
--------------	-------------------------------

Consumption (Standard)	98W	
Consumption (Standby)	≤1W	
Type	Internal	
Net Weight	28.5kg (62.8lb)	
Gross Weight	32kg (70.5lb)	
Bezel Width	25.5mm (U/L/R/B)	
Wall Mount	400×400mm (15.7"×15.7")	
Dimensions(no base)	1263.1×743.9×50.3mm (49.8"×29.3"×2.0")	
Package(W×H×D)	1430×920×200mm (56.3"×36.2"×7.9")	
Work Environment	Temperature	0°C~50°C (32°F~122°F)
	Humidity	20%~90%

#### Accessory

Standard	VGA cable, power cable, remote control
Optional	Pedestal, hanging bracket

#### Certifications

Certifications	CE/FCC
----------------	--------

Dimensions(mm)

