

# DH-IPC-HDPW5242G-Z-MF

2MP Pro AI IR Vari-focal Dome Network Camera



- 1/1.8" 2Megapixel progressive scan CMOS
- H.265 & H.264 triple-stream encoding
- 50/60 fps@1080P(1920 × 1080)
- WDR (140 dB), Day/Night (ICR), 3D DNR, AWB, AGC, BLC
- Multiple network monitoring: Web viewer, CMS (DSS/PSS) & DMSS
- 2.7 mm–12.0 mm motorized lens
- 1/1 Alarm in/out, 1/1 audio in/out
- Max. IR LEDs Length 40 m
- Micro SD memory



## System Overview

Pro AI series contains Face Detection, Perimeter Protection and People Counting functions. Powered by deep-learning Artificial Intelligence algorithms, significantly improved accuracy. Meanwhile, the series features starlight and smart IR technology.

## Functions

### Face Detection

Face Detection is a software application that automatically captures faces from within a digital image or a video frame from a video source. Dahua cameras use advanced deep learning algorithms and are trained by a large number of face data sources, enabling the camera to locate faces quickly and accurately from the video source and capture facial images.

### Face Attributes

Through the use of deep learning algorithms to analyze facial images, Dahua cameras can extract six facial attributes from each frame, including Age, Gender, Expression (Jolly/Surprise/Normal/Rage/Sad/Disgusted/Confused/Frightened), Glasses, Mouth Mask, Moustache & Beard. Customers can acquire data of interest via face attributes statistics.

### Perimeter Protection

Dahua's Perimeter Protection functions significantly improved accuracy. Perimeter Protection reduces false alarms and decreases pixel count requirements for object detection. Perimeter Protection features custom tripwires based on object type for automation in limited access areas such as pedestrian or vehicle-only zones. This combination of advanced AI analytics and real-time alerts to a desktop or to a mobile client reduces system requirements and resources resulting in greater surveillance system efficiency.

### People Counting

People Counting function uses advanced image processing technology to capture depth information from within images. The camera pairs this information with deep learning algorithms to analyze and detect human bodies and track target objects in real time. The camera provides statistics for separate individuals' entrance and exit with up to 95% counting accuracy.

### Metadata

Metadata is feature attribute information extracted from a target object which can be used for data retrieval. Dahua face detection camera can extract six facial attributes and output the metadata for analysis.

Technical Specification						
<b>Camera</b>						
Image Sensor	1/1.8" 2Megapixel progressive scan CMOS					
Effective Pixels	1920 (H) × 1080 (V)					
RAM/ROM	1 GB/128 MB					
Scanning System	Progressive					
Electronic Shutter Speed	Auto/Manual, 1/3 s–1/100000 s					
Minimum Illumination	0.003Lux@F1.8					
IR Distance	Distance up to 40 m (131 ft)					
IR On/Off Control	Auto/Manual					
IR LEDs	3					
<b>Lens</b>						
Lens Type	Motorized vari-focal					
Mount Type	Board-in					
Focal Length	2.7 mm–12.0 mm					
Max. Aperture	F1.8					
Angle of View	H: 114°–47°, V: 62°–26°					
Aperture Type	Auto					
Close Focus Distance	1.2 m (3.94 ft)					
DORI Distance	Lens	Detect	Observe	Recognize	Identify	
	W	41.0m (134.5ft)	16.4m (53.8ft)	8.2m (26.9ft)	4.1m (13.5ft)	
	T	93.4m (306.4ft)	37.3m (122.4ft)	18.6m (61.0ft)	9.3m (30.5ft)	
<b>Pan/Tilt/Rotation</b>						
Pan/Tilt/Rotation Range	Pan: 0°–355°; Tilt: 0°–75°; Rotation: 0°–355°					
<b>Artificial Intelligence</b>						
Face Detection	Support face image capture					
Face Attributes	Support 6 kinds of face attributes extraction: Age, Gender, Expression (Jolly, Surprise, Normal, Rage, Sad, Disgusted, Confused, Frightened), Glasses, Mouth Mask, Moustache & Beard					
Perimeter Protection	Tripwire, intrusion (Recognition of vehicle and people), fast moving, loitering detection, parking detection and people gathering					
People Counting	Support Line crossing/Region/Queueing people counting; Support 4 accesses independent detection, 4 areas independent detection					
<b>General Intelligence</b>						
Event Trigger	Motion detection, Video tampering, Scene changing, Network disconnection, IP address conflict, Illegal Access, Storage anomaly					
General Intelligence	Object Abandoned/Missing					
Heat Map	Yes					
<b>Video</b>						
Compression	H.265, H.264, H.264B, H.264H, MJPEG (sub stream)					
Smart Codec	Yes					
Streaming Capability	3 Streams					
Resolution	1080P (1920 × 1080)/1.3M (1280 × 960)/720P (1280 × 720)/D1 (704 × 576/704 × 480)/VGA (640 × 480)/CIF (352 × 288/352 × 240)					
Frame Rate	Main Stream: 1920 × 1080 (1 fps–50/60 fps)					
	Sub Stream: D1 (1 fps–25/30 fps) D1 (1 fps–50/60 fps)					
	Third Stream: 1080P (1 fps–16 fps)					
Bit Rate Control	CBR/VBR					
Bit Rate	H.264: 32 Kbps–8192 Kbps H.265: 19 Kbps–8192 Kbps					
Day/Night	Auto(ICR)/Color/B/W					
BLC Mode	BLC/HLC/WDR (140 dB)					
White Balance	Auto/Natural/Street Lamp/Outdoor/Manual					
Gain Control	Auto/Manual					
Noise Reduction	3D DNR					
Motion Detection	Off/On (4 Zone, Rectangle)					
Region of Interest	Off/On (4 Zone)					
Electronic Image Stabilization (EIS)	Yes					
Smart IR	Yes					
Defog	Yes					
Flip	0°/90°/180°/270°					
Mirror	Off/On					
Privacy Masking	Off/On (4 Area, Rectangle)					
<b>Audio</b>						
Compression	G.711a, G.711Mu, G.726, AAC, G.723					
<b>Network</b>						
Ethernet	RJ-45 (10/100 Base-T)					
Protocol	IPv4; IPv6; HTTP; HTTPS; TCP; UDP; ARP; RTP; RTSP; RTCP; RTMP; SMTP; FTP; SFTP; DHCP; DNS; DDNS; QoS; UPnP; NTP; Multicast; ICMP; IGMP; NFS; PPPoE; 802.1x; SNMP					
Interoperability	ONVIF (Profile S/Profile G/Profile T), CGI, Milestone, Genetec, P2P					
Streaming Method	Unicast/Multicast					
Max. User Access	20 Users					
Edge Storage	NAS; FTP; SFTP Micro SD card (support max. 256 G)					
Web Viewer	IE (versions newer than IE8), Chrome, Firefox, Safari (versions newer than Safari 12)					
Management Software	Smart PSS, DSS, DMSS					
Smart Phone	iOS, Android					
<b>Certifications</b>						
Certifications	CE-LVD: EN60950-1 CE-EMC: Electromagnetic Compatibility Directive 2014/30/EU FCC: 47 CFR FCC Part 15, Subpart B					

**Interface**

Audio Interface	1/1 channel In/Out
RS485	N/A
Alarm	1 channel In: 5mA 5V DC 1 channel Out: 300mA 12V DC

**Electrical**

Power Supply	DC 12V (±30%), PoE (802.3af) (Class 0)
Power Consumption	<11W

**Environmental**

Operating Conditions	-30° C to +60° C (-22° F to +140° F)/Less than 95% RH
Storage conditions	-30° C to +60° C (-22° F to +140° F)

**Construction**

Casing	plastic
Dimensions	Φ180.5 mm × 131.4 mm (7.11" × 5.17")
Net Weight	0.51 kg (1.12 lb)
Gross Weight	0.73 kg (1.61 lb)

**Ordering Information**

Type	Part Number	Description
4MP camera	DH-IPC-HDPW5142GP-Z-MF	2MP Pro AI IR Vari-focal Dome Network Camera, PAL
	DH-IPC-HDPW5142GN-Z-MF	2MP Pro AI IR Vari-focal Dome Network Camera, NTSC
	IPC-HDPW5142GP-Z-MF	2MP Pro AI IR Vari-focal Dome Network Camera, PAL
	IPC-HDPW5142GN-Z-MF	2MP Pro AI IR Vari-focal Dome Network Camera, NTSC
Accessories (optional)	PFA701	Junction Box

**Accessories**

**Optional:**





PFA701  
Junction Box

**In-ceiling Mount**

**Ceiling Mount**

PFA701



**Dimensions (mm[inch])**

