

DH-IPC-HFW5831E-ZE

8MP WDR IR Bullet Network Camera



- · 1/2.5" 8Megapixel progressive scan STARVIS™ CMOS
- · H.265&H.264 dual-stream encoding
- · 15fps@4K(3840×2160),25/30fps@3Mp(2304×1296)
- · Day/Night(ICR), 3DNR, AWB, AGC, BLC
- \cdot Multiple network monitoring: Web viewer, CMS(DSS/PSS) & DMSS
- · 2.7mm ~12mm motorized lens
- · Max. IR LEDs Length 50m
- · Micro SD memory, IP67, IK10, PoE















System Overview

With upgraded H.265 encoding technology, Eco-savvy series brings high efficient video compression capability. It can save bandwidth and storage. Meanwhile, the series features starlight, smart IR technology and intelligent image analysis techniques. This series supports reminder function, meanwhile fully protected from dust and water, certified to IP67 and vandal resistant to IK10 standard.

Functions

ePoE technology

The ePoE technology of Dahua, designed internally, adopts advanced 2D-PAM3 coding modulation from physical layer, and realizes full duplex transmission over 800 meters at the speed of 10Mbps, or 300 meters at the speed of 100Mbps via Cat 5 or coaxial cable media. Besides, it supports PoE and PoC power supply technology which has greatly simplified construction and wiring. Dahua ePoE technology offer a new way to accomplish long distance transmission between IP camera and network switch. It allows more flexible surveillance system design, improves reliability and saves construction and wiring cost.

4K technology

 $4 \mbox{K}$ technology as a revolutionary breakthrough in image, which enhance the expressive image of essence, allowing users to experience the best picture quality brought about by the visual feast . For the purposes of $4 \mbox{K}$ surveillance with four times the $1080 \mbox{P}$ resolution, presented to the user with more details . Under the same scenario by raising the pixels , reduce the camera cost.

Wide Dynamic Range

The camera achieves vivid images, even in the most intense contrast lighting conditions, using industry-leading wide dynamic range (WDR) technology. For applications with both bright and low lighting conditions that change quickly, true WDR (120 dB) optimizes both the bright and dark areas of a scene at the same time to provide usable video.

Intelligent Video System (IVS)

IVS is a built-in video analytic algorithm that delivers intelligent functions to monitor a scene for Tripwire violations, intrusion detection, and abandoned or missing objects. A camera with IVS quickly and accurately responds to monitoring events in a specific area. In addition to scene analytics, the camera supports face detection to quickly capture a face and upload the image to a server. The camera also offers tamper detection by recognizing a dramatic scene change and generating a warning message to inspect the camera.

Protection(IP67, IK10, wide voltage)

The camera allows for $\pm 30\%$ input voltage tolerance, suitable for the most unstable conditions for outdoor applications. Its 6KV lightning rating provides effective protection for both the camera and its structure against lightning. Subjected and certified to rigorous dust and immersion tests (IP67) and impact tests (IK10), the camera is the choice for installation in even the most unforgiving environments.

Smart H.265+

Smart H.265+ is the optimized implementation of the H.265 codec that uses a scene-adaptive encoding strategy, dynamic GOP, dynamic ROI, flexible multi-frame reference structure and intelligent noise reduction to deliver high-quality video without straining the network. Smart H.265+ technology reduces bit rate and storage requirements by up to 70% when compared to standard H.265 video compression.



Technical Specification	Technical Specification						Devi/Allielia	A. t-1/CD) / C-1 / D/W
Marco	Technical Specification							
### Part			1/2 F# 0M					
SUM	_							
Seaning System								
Protection Shuter's peed	RAM/ROM						Noise Reduction	3D DNR
Minimum lilumination Distance Distanc	Scanning System		Progressive				Motion Detetion	Off / On (4 Zone, Rectangle)
Mainthum Maniform May	Electronic Shutter Speed						Region of Interest	Off / On (4 Zone)
Mathematical plataness Mathematical plata	Minimum Illumi	nation	0.2Lux/F1.4 (Color,1/30s,30IRE)				_	N/A
Ro No file	S/N Ratio		More than 50dB				Smart IR	Support
Rice	IR Distance		Distance up to 50m (164ft)				Defog	N/A
	IR On/Off Contro	ol	Auto/ Manual				Digital Zoom	16x
Lens Type	IR LEDs		4				Flip	0°/90°/180°/270°
Mount Type	Lens						Mirror	Off / On
Focal Length	Lens Type		Motorized/ A	uto Iris(DC)			Privacy Masking	Off / On (4 Area, Rectangle)
Focal Length			Board-in				Audio	
Angle of View							Compression	G.711a/ G.711Mu/ AAC/ G.726
Protocol	Max. Aperture		F1.4				Network	
Protocol FPE, DNCP, DNS, DNS, PROED; IPA4/PG, GOS; DNS, PROED; INC. PNS, DNS, PROED; IPA4/PG, GOS; DNS, PROED; INC. PNS, DNS, DNS, DNS, DNS, DNS, DNS, DNS, D	Angle of View		H:110°~40°, V:58°~23°				Ethernet	RJ-45 (10/100Base-T)
Close Focus Distance							Protocol	FTP; DHCP; DNS; DDNS; PPPOE; IPv4/v6; QoS;
Lens								IGMP; SNMP
DORI Distance W 85m(280ft) 34m(112ft) 7m(56ft) 8.5m(28ft) 45m(28ft) Max. User Access 10 Users/20 Users Pan/Tilt/Rotation Pan/Original Pan/Origi						Identify	Interoperability	ONVIF, PSIA, CGI
T 228m(748ft) 91m(299ft 46m(151ft) 23m(75ft)						•	Streaming Method	Unicast / Multicast
Pan/Tilt/Rotation Edge Storage Local PC for instant recording Mirco SD card 1286B Pan/Tilt/Rotation Range Pan:0°~360°; Tilt:0°~90°; Rotation:0°~360° Web Viewer IE, Chrome, Firefox, Safari Intelligence IVS Tripwire, Intrusion, Object Abandoned/Missing Management Software Smart PSS, DSS, Easy4ip Video Compression H.265+H.264+H.264 Certifications Certifications CE (EN 60950:2000) UI:UL60950-1 FCC: FCC Part 15 Subpart B Streaming Capability 3 Streams AK(3840×2160)/ 6M(3072×2048)/SM(3072×1728)/ 5M(2592×1944)/ 4M(2688×1520)/ 3M(2048x1536)/ 3M(2048x153	Distance	Т		91m(299ft		23m(75ft)	Max. User Access	10 Users /20 Users
Intelligence	Pan/Tilt/Rotation			Edge Storage	Local PC for instant recording			
NS	Pan/Tilt/Rotation Range		Pan:0°~360°;	Tilt:0°~90°; Ro	tation:0°~360)°	Web Viewer	IE, Chrome, Firefox, Safari
NS	Intelligence						Management Software	Smart PSS, DSS, Easy4ip
Advanced Intelligent Functions Face Detection Video Certifications Compression H.265+/H.265/H.264+/H.264 Certifications Streaming Capability 3 Streams 4K(3840×2160)/ 6M(3072×2048)/5M(3072×1728)/5M(2592×1944)/4M(2688×1520)/3M(2048×1536)/3M(2304×1296)/1080P(1920×1080)/1.3M(128 0x960)/720P(1280×720)/D1704×567/04×480)/VGA(640×480)/CIF(352×288/352×240) Video Interface N/A Audio Interface 1/1 channel In/Out N/A Frame Rate Sub Stream: 4K(1~15fps)/3M(1~25/30fps) RS485 N/A Frame Rate Sub Stream: D1(1~25/30fps) Alarm 2 channel In: 5mA 5VDC 1 channel Out: 300mA 12VDC Third Stream: 720P(1~25/30fps) Electrical Bit Rate Control CBR/VBR Power Supply DC12V, PoE (802.3af)(Class 0)	IVS		Tripwire, Intru	usion, Object A	Abandoned/N	1issing	-	IOS. Android
Video CE (EN 60950:2000) Compression H.265+/H.264+/H.264 Certifications CE (EN 60950:2000) Streaming Capability 3 Streams Interface Resolution 4K(3840×2160)/ 6M(3072×2048)/5M(3072×1728)/ 5M(2592×1944)/ 4M(2688×1520)/ 3M(2048×1536)/ 3M(2304×1296)/ 1080P(1920×1080)/1.3M(128 0×960)/720P(1280×720)/ D1(704×576/704×480)/ VGA(640×480)/ CIF(352×288/352×240) Video Interface N/A Audio Interface 1/1 channel In/Out 1/1 channel In/Out Frame Rate Sub Stream: 4K(1~15fps)/3M(1~25/30fps) RS485 N/A Frame Rate Sub Stream: D1(1~25/30fps) Alarm 2 channel In: 5mA 5VDC 1 channel Out: 300mA 12VDC Third Stream: 720P(1~25/30fps) Electrical Bit Rate Control CBR/VBR Power Supply DC12V, PoE (802.3af)(Class 0)	Advanced Intelli	gent Functions	Face Detection	n				,
Compression	Video						certifications	CE (FN 60950:2000)
Streams	Compression		H.265+/H.265	5/H.264+/H.26	54		Certifications	UL:UL60950-1
SM(2592×1944)/ 4M(2688×1520)/ 3M(2048×1536)/ 3M(2304×1296)/ 1080P(1920×1080)/1.3M(128 0x960)/ 720P(1280x720)/ D1(704×576/704×480)/ VGA(640×480)/ CIF(352×288/352×240)	Streaming Capability						Interface	,
Nesolidion			5M(2592×1944)/ 4M(2688×1520)/ 3M(2048×1536)/ 3M(2304×1296)/ 1080P(1920×1080)/1.3M(128 0x960)/ 720P(1280×720)/ D1(704×576/704×480)/					N/A
Frame Rate Sub Stream: D1(1~25/30fps) Alarm 2 channel In: 5mA 5VDC 1 channel Out: 300mA 12VDC Third Stream: 720P(1~25/30fps) Electrical Bit Rate Control CBR/VBR Power Supply DC12V, PoE (802.3af)(Class 0)	กะรูปเนเบา							
Third Stream: 720P(1~25/30fps) Bit Rate Control CBR/VBR 1 channel Out: 300mA 12VDC Electrical Power Supply DC12V, PoE (802.3af)(Class 0)			Main Stream: 4K(1~15fps)/3M(1~25/30fps)				RS485	N/A
Third Stream: 720P(1~25/30fps) Electrical Bit Rate Control CBR/VBR Power Supply DC12V, PoE (802.3af)(Class 0)	Frame Rate							2 channel In: 5mA 5VDC
PUBLISHED AND ADDRESS AND ADDR			Third Stream: 720P(1~25/30fps)				Electrical	
Bit Rate H.264: 24K ~ 10240Kbps H.265: 14K ~ 9984Kbps Power Consumption <12.95W	Bit Rate Control		CBR/VBR				Power Supply	DC12V, PoE (802.3af)(Class 0)
	Bit Rate		H.264: 24K ~ 3	10240Kbps H.	.265: 14K ~ 99	84Kbps	Power Consumption	<12.95W

Environmental

Operating Conditions	-30° C ~ +60° C (-22° F ~ +140° F) / Less than 95% RH
Strorage Conditions	-30° C ~ +60° C (-22° F ~ +140° F) / Less than 95% RH
Ingress Protection	IP67
Vandal Resistance	IK10

Construction

Casing	Metal
Dimensions	273.2mm×95.0mm×95.0mm (10.76"×3.74"×3.74")
Net Weight	1.11Kg (2.44lb)
Gross Weight	1.51Kg (3.33lb)

Ordering Information				
Туре	Part Number	Description		
	DH-IPC- HFW5831EP-ZE	8MP IR Bullet Network Camera, WDR, PAL		
OMAD and a second	DH-IPC- HFW5831EN-ZE	8MP IR Bullet Network Camera, WDR, NTSC		
8MP camera	IPC-HFW5831EP- ZE	8MP IR Bullet Network Camera, WDR, PAL		
	IPC-HFW5831EN- ZE	8MP IR Bullet Network Camera, WDR, NTSC		
	PFA121	Junction box		
Accessories (optional)	PFA152-E	Pole Mount		
	LR1002	ePoE Over Coax Converter		

Accessories

Optional:







PFA121 Junction box

PFA152-E Pole Mount

LR1002 ePoE Over Coax Converter

Junction Mount	Pole Mount
PFA121	PFA121 + PFA152-E

273.2 [10.76"] 174.4 [6.87"] 160.0 [6.3"]

