

# DHI-IVSS7016R-4M

## 3U 16HDDs WizMind Intelligent Video Surveillance Server



**WizMind**

Launched by Dahua Technology, Dahua WizMind is a full portfolio of solutions composed of project-oriented products including IPC, NVR, PTZ, XVR, Thermal and software platform which adopts industry-leading deep learning algorithms. Focusing on customer's requirements, WizMind provides precise, reliable and comprehensive AI solutions for verticals.

### Series Overview

Dahua IVSS goes beyond the ordinary NVR products. It is an Intelligent Video Surveillance Server that combines video management features with traditional video storage functions in one device. Besides the basic functions as a network video recorder, IVSS is integrated with features such as face detection and face recognition for different business and industrial applications.

With the build-in deep learning module, IVSS series products adopt video image metadata technology based on deep learning algorithms, offering high-precision human face recognition and perimeter protection. By applying deep learning artificial intelligence, IVSS allows users to focus on what matters most, to improve event response time and help make video actionable.

An all new UI design supports device operation and maintenance management, improving the value and experience of surveillance view, and serving the era of security big data.

### Functions

#### Face Recognition


Supports recording faces by metadata and real-time crosscheck with incredible accuracy to figure out the face with target features. With the Regular and Stranger face mode, IVSS triggers various kinds of alarm actions for different applications.

#### AI IVS

With deep learning algorithm, AI IVS technology can recognize human and vehicle accurately. In restricted area (such as pedestrian area and vehicle area), the false alarms of intelligent detection based on target type (such as tripwire, intrusion, parking detection, loitering detection and crowd gathering estimation) are largely reduced.

- Industry embedded micro-controller
- Max 576 Mbps incoming bandwidth
- 256-channel IP video access
- Up to 48-channel perimeter protection
- Up to 48-channel face recognition with normal IPC
- Up to 160-channel face recognition with face detection IPC
- Up to 48-channel video metadata
- Up to 50 face databases with 1000,000 face pictures in total
- Supports RAID 0/1/5/6/10/50/60
- SAS3.0 for storage extension

#### Redundant power



#### Video Metadata

Metadata is feature attribute information extracted from a target object which can be used for data retrieval. Currently, there are four main kinds of metadata in the security industry: Human face, human body, and motor vehicle and non-motor vehicle metadata.

#### AI Search

Supports search by metadata of human and vehicles. Supports uploading face pictures to IVSS and compare them with recorded faces in IVSS by similarity. IVSS enables operators to quickly and easily search through multiple channels and long duration, to efficiently find out when and where a person of interest appeared.

#### ANPR

Automatic Number Plate Recognition available for convenient entrance/exit management. This feature provides number plate recognition (working with Dahua ITC camera), number plate comparison with blocklist/allowlist, vehicle database management, and vehicle record search.

#### N+M Hot Standby

The highly reliable redundancy N+M Hot Standby design provides a secure failover technique to ensure immediate backup. In the event of a system failure, the sub device instantly takes over the main device to ensure no data loss.

#### Fisheye Dewarp

Supports multiple fisheye dewarp modes to make viewing video easy whether its live or during playback.

#### Smart Tracking

The automatic tracking PTZ feature automatically tracks a moving target throughout the camera's field of view. This function is ideal for following an object as it moves through airports, parking lots, city centers, or other scenes.

### Technical Specification

#### System

Main Processor	Industry embedded micro-controller
Operating System	Embedded Linux OS
Operation Interface	WEB (PCAPP), local GUI

#### AI Applications

AI by Camera	Face detection, face recognition, video metadata, IVS (tripwire, intrusion, abandoned object, missing object, fast moving, parking detection, crowd gathering, loitering, parking, and fence-crossing), people counting, smoking detection, call detection
AI by Device	Face detection, face recognition, video metadata, IVS (tripwire, intrusion, crowd gathering, loitering detection, parking detection), plate comparison

#### Perimeter Protection

IVS Performance (AI by Device) (Channel Number)	Advanced model: 48-channel
IVS Performance (AI by Camera) (Channel Number)	256-channel

#### Human Face Detection

Human Face Properties	Supports 6 properties: Gender, age range (6 levels), glasses, expression (8 types), mouth mask, and beard
Face Detection Performance (AI by Device) (1080P) (Channel Number)	48-channel
Face Detection Performance (AI by camera) (Channel Number)	160-channel

#### Human Face Recognition

Face Database Capacity	50 face databases with 1000,000 face pictures in total
Human Face Recognition Performance (AI by Device) (1080P)(Channel Number)	48-channel with normal IP camera 160-channel with face detection IP camera (Totally 160 face pictures analyzed per second)
Human Face Recognition Performance (AI by camera) (Channel Number)	160-channel

#### ANPR

Plate Database Capacity	50 plate databases with 500,000 plate numbers in total Supports allowlist and blocklist
Plate Detection Performance by ITC Camera (Channel Number)	48-channel

#### Video Metadata

Human Body Properties	Gender, age, sleeves length, top color, bottom type, bottom color, bag, rain coat, umbrella, hat, hairstyle, direction, hold a baby, mouth mask
Vehicle Properties	Vehicle type, vehicle color, plate color, logo, calling, seatbelt, ornament, region
Non-motorized Vehicle Properties	Non-motor Vehicle type, non-motor vehicle color, number of passengers, umbrella, rain coat, bag, sleeve length, top color, hat, hair style, mouth mask
Metadata Performance (AI by Device) (1080P) (Channel Number)	48-channel

Metadata Performance (AI by camera) (Channel Number)	64-channel
--	------------

#### Video Parameters

Remote Connection	256-channel
Network Bandwidth	Incoming bandwidth: 576 Mbps recording bandwidth: 576 Mbps outgoing bandwidth: 128 Mbps
Resolution	24MP/16MP/12MP/8MP/6MP/5MP/4MP/3MP/1080p/960p/720p/D1/CIF/QCIF
Decoding Capability	2-channel 24MP/3-channel 16MP/6-channel 12MP (20 fps)/7-channel 12MP (15 fps)/6-channel 8MP (30 fps)/12-channel 8MP (15 fps)/7-channel 6MP (30 fps)/9-channel 5MP (30 fps)/11-channel 5MP (25 fps)/12-channel 4MP (30 fps)/18-channel 4MP (20 fps)/19-channel 3MP (25 fps)/12-channel 1080p (60 fps)/24-channel 1080p (30 fps)/36-channel 720p (30 fps)
Video Output	1-channel VGA output, 3-channel HDMI output, VGA 1/HDMI 1 outputs the same video source Supports 4K output
Multi-screen Display	Customized display Max. 36-channel local live view Max. 16-channel PCAPP live view
Third-party Support	Onvif; RTSP; Sony; Panasonic; Axis; Arecont; Pelco; Canon; Samsung
Operating System	Embedded Linux OS
Operation Interface	WEB (PCAPP), local GUI

#### Compression

Video Compression	Smart H.265+; Smart H.264+; H.265; H.264
Audio Compression	G.711A; G.711U; PCM; G726

#### Network

Protocol	HTTP; HTTPS; TCP/IP; IPv4; RTSP; UDP; SMTP; NTP; DHCP; DNS; DDNS; P2P
Mobile Phone	iOS, Android
Interoperability	ONVIF (Profile S, T, G and Q); CGI; SDK
Browser	Chrome; PCAPP; IE9 or higher; Firefox
Network Mode	NIC binding mode such as multiple-address mode, load balance, fault-tolerance, etc

#### Record Playback

Multiple-channel Playback	Max. 16-channel playback
Record Search	Search video detection/manual record/IO alarm/intelligent event/all record file
Storage Medium	Internal HDD, SAS disk array enclosure
Backup Method	HDD, peripheral USB storage device
Playback Function	Play, pause, stop, fast forward, fast backward, reverse play, frame by frame play Full-screen, backup (clip/file), snapshot, digital zoom, audio on/off

#### Storage

HDD Group	16
RAID	RAID 0/1/5/6/10/50/60
Storage Pool	N/A

#### Alarm

General Alarm	Motion detect, tampering, local alarm
---------------	---------------------------------------

Anomaly Alarm	IPC offline alarm, storage error, HDD full, IP conflict, MAC conflict, login lock, AI module temperature alarm, AI module offline, fan malfunction
Intelligent Alarm	Human face detection, human face recognition, entries frequency, video metadata (person/vehicle/non-motor vehicle), IVS, plate recognition, people counting, smoking, call
Alarm Linkage	Record, snapshot (full image), local external alarm output, IPC external alarm output, access & control, audio prompt, buzzer, log, preset, email

**Peripheral Interface**

Audio Input	1-channel (reserved)
Audio Output	1-channel, speaker output, audio linkage output
Alarm Input	16-channel
Alarm Output	8-channel
Internal HDD	16 slots, SATA3.0/SAS. Max. 16T/HDD
eSATA	1 port
SAS	2 SAS3.0 ports
RS-232	1 port, for debug or transparent COM data
RS-485	1 port, control peripheral PTZ and so on Supports various protocols
USB	4 ports 2 USB2.0 ports at the front panel and 2 USB3.0 ports at the rear panel
HDMI	3 ports; support 4K output
VGA	1 port
Network	4 RJ-45 10/100/1000 Mbps self-adaptive Ethernet ports
Power	2 ports
PoE	N/A

**General Parameters**

Power Supply	AC100-127V/AC200-240V 50/60Hz
Power Consumption	120W (without HDD, idling) 312W (all HDDs connected)
Net Weight	16 kg (35.27 lb)
Gross Weight	17 kg (37.48 lb)
Dimensions (W x L x H)	Chassis: 444.8 mm x 539.4 mm x 133.2 mm (17.51 " x 21.24 " x 5.24 ") Max. size: 485.0 mm (with hanger) x 539.4 mm x 133.2 mm (with feet mat) (19.09 " x 21.24 " x 5.24 ")
Packaging Dimensions (W x L x H)	689 mm x 779 mm x 464 mm (27.13 " x 30.67 " x 18.27 ")
Operating Conditions	0 °C to +45 °C (+32 °F to +113 °F)/10%RH-90% RH
Storage Conditions	0 °C to +40 °C (+32 °F to +104 °F)/30%RH-85% RH
Operating Altitude	5000 m (16404.20 ft)
Installation Mode	Desktop/rack
Certifications	CE: CE-LVD: EN 60950-1/IEC 60950-1 CE-EMC: EN55024,EN55035, EN50130-4,EN60950-1 FCC: Part 15 Subpart A UL: 60950-1 and CAN/CSA C22.2 No. 60950-1-07

**Dimensions (mm[inch])**

