

DH-TPC-BF8421

Thermal Network Hybrid Bullet Camera



- 640x512 VOx uncooled thermal sensor technology
- Athermalized lens (thermal camera), focus-free
- Support ROI, motion detection, color Palettes
- Support fire detection & alarm
- Built-in 2/2 alarm in/out
- Micro SD memory, IP67



System Overview

Featuring a dual lens fixed bullet camera, this series provides an all-in-one solution that is especially beneficial for long distance video surveillance in outdoor applications. Together with Dahua Thermal and Starlight technology, the camera's long range capabilities are able to be utilized even at night. The series combines one thermal camera for monitoring in total darkness and one camera with Starlight functionality and a motorized lens for confirming details up close.

Functions

Uncooled Vox Technology

Dahua thermal cameras use uncooled Vox sensor technology. Because of small size and better performance, it's cost-effective solution for thermal security.

High Sensitivity

High thermal sensitivity(<40mK) makes cameras capture more image details and temperature difference information.

Fire Detection & Alarm

With built-in Fire detect function, the camera has the ability to detect fire in a long distance. because thermal camera is sensitive to temperature, so the accuracy of fire detection will be higher than visible camera.

Intelligent Video System (IVS)

With built-in intelligent video analytics, the camera has the ability to detect and analyze moving objects for improved video surveillance. The camera provides optional standard intelligence at the edge allowing detection of multiple object behaviors such as abandoned or missing objects. IVS also supports Tripwire analytics, allowing the camera to detect when a pre-determined line has been crossed.

Environmental

With a temperature range of -40 °C to +70 °C (-40 °F to +158 °F), the camera is designed for extreme temperature environments. Subjected and certified to rigorous dust and water immersion tests, the IP67 rating makes it suitable for demanding outdoor applications. Product can meet MIL-STD-810G (High temperature, Low temperature, Temperature shock, Rain, Humidity, Sand and dust) standards.

Protection

Supporting ±15% input voltage tolerance, this camera suits even the most unstable conditions for outdoor applications. Its 6KV lightning rating provides protection against the camera and its structure from the effects of lightning.

Technical Specification				
General				
Structure		Multi-sensor bullet camera		
Thermal				
Detector Type		Vanadium oxide uncooled focal plane detector		
Effective Pixels		640 × 512		
Pixel Pitch		17μm		
Spectral Range		8μm–14μm		
Thermal Sensitivity (NETD)		≤40mK		
Focal Length		25mm; 35mm; 50mm; 75mm; 100mm		
Field of View		25mm: horizontal: 24.6°; vertical: 19.8° 35mm: horizontal: 17.6°; vertical: 14.1° 50mm: horizontal: 12.4°; vertical: 9.9° 75mm: horizontal: 8.3°; vertical: 6.6° 100mm: horizontal: 6.2°; vertical: 5.0°		
Focus Mode		Manual		
Aperture		25mm/35mm/50mm/75mm: F1.0 100mm: F1.4		
DRI	Lens	Detect	Recognize	Identify
	25mm	vehicle: 1961m (6433.65 ft) human: 735 m (2411.39 ft)	vehicle: 490m (1607.60ft) human: 189m (620.07ft)	vehicle: 245m (803.80 ft) human: 95 m (311.68 ft)
	35mm	vehicle: 2745 m (9005.80 ft) human: 1029 m (3375.94 ft)	vehicle: 686m (2250.63ft) human: 265m (869.41ft)	vehicle: 343m (1125.31 ft) human: 132 m (433.07 ft)
	50mm	vehicle: 3922m (12867.30 ft) human: 1471 m (4826.06 ft)	vehicle: 980m (3215.18ft) human: 378m (1240.14ft)	vehicle: 490m (1607.60 ft) human: 189 m (620.07 ft)
	75mm	vehicle: 5882m (19297.67 ft) human: 2206 m (7237.44 ft)	vehicle: 1471m (4826.06ft) human: 567m (1860.21ft)	vehicle: 735m (2411.39 ft) human: 284 m (931.74 ft)
	100mm	vehicle: 7843m (25731.31 ft) human: 2941 m (9648.83 ft)	vehicle: 1961m (6433.65ft) human: 756m (2480.28ft)	vehicle: 980m (3215.18 ft) human: 378 m (1240.14 ft)
DRI values are based on the reference: human (1.8 m × 0.5 m) vehicle (4 m × 1.4 m)				
Digital Detail Enhancement (DDE)		Yes		
AGC		Auto; manual		
Noise Reduction		2D NR; 3D NR		
Color Palettes		18 color modes selectable such as Whitehot/Blackhot/Ironrow/Icefire		
Visible				
Image Sensor		1/2.8 inch CMOS		
Effective Pixels		1920 x 1080		
Max. Resolution		2MP		
Horizontal Definition		≥1083TVL		
Min. Illumination		Color: 0.005 Lux@F1.6; black & white: 0.00051 Lux@F1.6; IR light on: 0 Lux		
AGC		Auto; manual		

Noise Reduction	2D NR; 3D NR
S/N Ratio	>55 dB
White Balance	Auto/manual/indoor/outdoor/tracking/sodium lamp/natural/street light
Electronic Defog	Yes
Electronic Image Stabilization (EIS)	Yes
Electronic Shutter Speed	1/1s–1/100000s (auto or manual)
BLC	Yes
WDR	Yes
HLC	Yes
Day/Night	Auto (ICR); color/B/W
Focus Mode	Auto; semi-auto; manual
Focal Length	3.95mm–177.7mm
Field of View	3.95mm:horizontal: 70.3°; vertical: 43.3°; diagonal: 77.92° 177.7mm:horizontal: 1.8°; vertical: 1.0°; diagonal: 2.06°
DORI Distance	D: 2345 m (7694 ft); O: 938 m (3077 ft); R: 469 m (1539 ft); I: 234 m (768 ft)
Close Focus Distance	100 mm–1000 mm
Optical Zoom	45x
Aperture	F1.6–F4.95
IR Fill Light Control	Auto; manual
Max Fill Light Distance	≥100 m
Audio and Video	
Video Compression	H.265; H.264M; H.264H; H.264B; MJPEG
Resolution	Thermal: Main stream 1280 × 1024/1280 × 720/640 × 512, 1280 × 1024 by default; sub stream 640 × 512/320 × 256, 640 × 512 by default Visible: 1080P (1920 × 1080)/720P (1280 × 720) /D1 (704 × 576/704 × 480)/CIF (352 × 288/352× 240)
Video Frame Rate	50Hz: Main stream (1280 x 1024@25fps/1280 × 720@25fps/640 × 512@25fps), 1280 x 1024@25fps by default; sub stream (640 × 512@25fps/320 x 256@25fps), 640 x512@25fps by default 60Hz: Main stream (1280 x 1024@30fps/1280 × 720@30fps/640 × 512@30fps), 1280 x 1024@30fps by default; sub stream (640 × 512@30fps/320*256@30fps), 640 x512@30fps by default
Audio Compression	G.711a; G.711mu; AAC; PCM
Image Encoding Format	JPEG
General Function	
Two-way Talk	Yes
Network Protocol	HTTP; TCP; ARP; RTSP; RTP; UDP; RTCP; SMTP; FTP; DHCP; DNS; DDNS; PPPOE; IPv4/v6; SNMP; QoS; UPnP; NTP
Region of Interest (ROI)	Yes
Edge Storage	FTP; micro SD card (256G, hot plug)
Interoperability	ONVIF; CGI; PSIA; Dahua SDK

Browser	IE: IE8 and the later, and explorer with IE core Google: 42 and the earlier Firefox: 42 and the earlier Safari: 10 and the earlier
User/Host	20 channels at most (the total bandwidth 64M)
Security	Authorized username and password; attached MAC address; encrypted HTTPS; IEEE 802.1x; controlled network access
User Management	Support 20 users at most and users are classified as two groups--administrator group and user group.
Malfunction Detection	Network disconnection; IP addresses conflict; SD card error (status or storage space);

Smart Event

General IVS Analytics	Tripwire/intrusion
-----------------------	--------------------

Professional and Intelligent

Fire Detection	Yes
Cold/Hot Spot Trace	Auto tracking of the hottest spot and the coldest spot in the thermal image
IVS Analytics	Tripwire/intrusion

Port

Network	1 10M/100M Ethernet port (RJ-45)
Alarm Input	2 channels
Alarm Output	2 channels
Audio Input	1 channel
Audio Output	1 channel
RS-485	1 channel

Power

Power Supply	24V AC/3A±15%, 50/60HZ, PoE + (802.3 at)
Power Consumption	Basic power consumption: 16W (24V AC, LED light off) Max power consumption: 28W (24V AC, LED light on)

Environment

Operating Temperature	-40°C to +70°C (-40°F to +158°F)
Operating Humidity	≤95%
Self-adaptive	Auto heating to protect the chip under the cold environment


Physical Characteristics

Protection Grade	IP67, anti-surge 6KV, anti-electrostatic 8KV (touched by objects), anti-electrostatic 15KV (air)
Dimensions	435.6mmx248.4mmx373.5mm (17.15"x9.80"x14.70")
Packaging Dimensions	557mmx442mmx371mm (22.00"x17.40"x14.61")
Net Weight	<9KG (<19.84lb)
Gross Weight	<14KG (<30.86lb)
Power Adaptor	Contained
Lens	Contained

Certification

Certifications	CE (EN 60950:2000); FCC (FCC Part 15 SubpartB) IEC 60068-2-30\ IEC 60068-2-52
----------------	---

Installation Diagram (Wall Mount)



Dimensions (mm[inch])

