

DH-TPC-PT8621A-T

Thermal Network Hybrid Pan & Tilt Camera



- 640x512 VOx uncooled thermal sensor technology
- Athermalized lens(thermal), focus-free
- 1/1.8" 4 megapixel progressive scan CMOS
- Support detection and alarm of fire and smog
- Max 140°/s pan speed, 360° endless pan rotation
- Up to 300 presets, 5 auto scan, 8 tour, 5 pattern
- 7/2 alarm in/out
- Micro SD memory, IP66
- Laser range finder(optional)
- Laser illuminator(optional)

System Overview

Featuring a dual lens Pan-Tilt camera, this series provides an all-in-one solution that is especially beneficial for long distance video surveillance in outdoor applications. Together with Dahua Thermal and Starlight technology, the camera's long range capabilities are able to be utilized even at night. The series combines one thermal camera for monitoring in total darkness and one camera with Starlight functionality and a lens for confirming details up close.

Functions

Uncooled Vox Technology

Dahua thermal cameras use uncooled Vox sensor technology. Their small size and better performance make them a cost-effective solution for thermal security.

High Sensitivity

High thermal sensitivity ($\leq 40\text{mK}$) allows cameras to capture more image details and temperature difference information.

Fire Detection & Alarm

With built-in fire detection functionality, the camera has the ability to detect fires from long range. Because thermal cameras are sensitive to temperature, they provide higher fire detection accuracy than General Camera, making them particularly fit for applications such as forest fire prevention.

Intelligent Video System (IVS)

IVS is a built-in video analytics algorithm that delivers intelligent functions to monitor a scene for tripwire violations, intrusion detection, and abandoned or missing objects. A camera with IVS quickly and accurately responds to monitoring events in a specific area.

Environmental

With a temperature range of $-40\text{ }^{\circ}\text{C}$ to $+70\text{ }^{\circ}\text{C}$ ($-40\text{ }^{\circ}\text{F}$ to $+158\text{ }^{\circ}\text{F}$), the camera is designed for extreme temperature environments. Subjected and certified to rigorous dust and water immersion tests, the IP66 rating makes it suitable for demanding outdoor applications. For environments with rain, sleet, snow and fog, an integrated wiper(optional) provides users with clear visibility at all times. Product can meet IEC 60068-2-30\IEC 60068-2-52 standards.

Protection

The camera Supporting wide range voltage input (100-300V AC), suitable for the most unstable conditions for outdoor applications. Its 6 kV lightning rating provides effective protection for both the camera and its structure against lightning.

Technical Specification				
Thermal				
Detector Type		Vanadium oxide uncooled focal plane detector		
Effective Pixels		640×512		
Pixel Pitch		17μm		
Spectral Range		8μm–14μm		
Thermal Sensitivity (NETD)		≤40mK		
Focal Length		50mm, 75 mm, 100 mm		
Field of View		50mm: horizontal: 12.4°, vertical: 9.9° 75mm: horizontal: 8.3°, vertical: 6.6° 100mm: horizontal: 6.2°, vertical: 5.0°		
Focus Mode		Fixed		
Detection Distance	Lens	Detection	Recognition	Identification
	50 mm	Vehicle: 3922 m (12867.45 ft) Human: 1471 m (4826.12 ft)	Vehicle: 980 m (3215.22 ft) Human: 378 m (1240.16 ft)	Vehicle: 490 m (1607.61 ft) Human: 189 m (620.08 ft)
	75 mm	Vehicle: 5882 m (19297.90 ft) Human: 2206 m (7237.53 ft)	Vehicle: 1471 m (4826.12 ft) Human: 567 m (1860.24 ft)	Vehicle: 735 m (2411.42 ft) Human: 284 m (931.76 ft)
	100 mm	Vehicle: 7843 m (25731.63 ft) Human: 2931 m (9616.14 ft)	Vehicle: 1961 m (6433.73 ft) Human: 756 m (2480.31 ft)	Vehicle: 980 m (3215.22 ft) Human: 378 m (1240.16 ft)
Digital Detail Enhancement (DDE)		Yes		
Thermal Image Stabilization		Electronic Image Stabilization		
AGC		Auto; manual		
Noise Reduction		2D NR; 3D NR		
Color Palettes		18 color modes selectable such as Whitehot/Blackhot/Ironrow/Icefire.		
Visible				
Image Sensor		1/1.8 inch CMOS		
Max. Resolution		2560x1440		
Visible Effective Pixels		4MP		
Min. Illumination		Color: 0.001 Lux@F1.4 (1/30s, 30IRE) Black & white: 0.0001 Lux@F1.4 0 Lux (IR on)		
AGC		Auto; manual		
Noise Reduction		2D NR; 3D NR		
S/N Ratio		≥ 55 dB		
White Balance		Auto/manual/indoor/outdoor/tracking/sodium lamp/street lamp/natural		
Defog		Optical Defog		
Visible Image Stabilization		Optical Image Stabilization		
Electronic Shutter Speed		1/30000s–1s		
BLC		Yes		
WDR		Yes		
HLC		Yes		
Digital Zoom		16×		
Day/Night		Auto (ICR); color/B/W		
Iris		Auto		
Focus Mode		Auto; semi-auto; manual		
Focal Length		6 mm–336 mm		
Field of View		6 mm: horizontal: 64.4°; vertical: 38.37°; 336 mm: horizontal: 1.28°; vertical: 0.72°;		
Close Focus Distance		10 mm–1500 mm		
Optical Zoom		56×		
Aperture		F1.4–F4.5		
Laser Illuminator(Optional)				
Wavelength		850±5nm		
Distance		800m		
Laser Range Finder(Optional)				
Wavelength		1570nm(eyesafe)		
Distance		1000m		
Accuracy		±2m		
Audio and Video				
Video Compression		H.265; H.264M; H.264H; H.264B; MJPEG		
Resolution		Thermal: SXGA(1280×1024)/720P(1280×720) / 640×512/320×256 Visual: 4M (2560×1440)/1080P (1920×1080)/720P (1280×720)/D1 (704×576/704×480) /CIF (352×288/352×240)		
Video Frame Rate		Thermal: 50Hz: Main stream (1280×1024@25fps/1280×720@25fps/640×512@25fps), sub stream (640×512@25fps/320×256@25fps) 60Hz: Main stream (1280×1024@30fps/1280×720@30fps/640×512@30fps), sub stream (640×512@30fps/320×256@30fps) Visual: 50Hz: Main stream (2560×1440@25fps/1920×1080@25fps/1280×720@25fps/704×576@25fps), sub stream (704×576@25fps/352×288@25fps) 60Hz: Main stream (2560×1440@30fps/1920×1080@30fps/1280×720@30fps/704×480@30fps), sub stream (704×480@30fps/352×240@30fps)		

Audio Compression	G.711a; G.711mu; PCM
Image Encoding Format	JPEG

PTZ

Pan/Tilt Range	Pan: 0°–360° endless; Tilt: -90°–45°
Manual Control Speed	Pan: 0.1°–140°/s; Tilt: 0.1°–50°/s
Preset Speed	Pan: 0.1°–80°/s; Tilt: 0.1°–60°/s
Preset	300
PTZ Mode	5 Auto Scan, 8 Tour, 5 Pattern, Auto Pan
Speed Setup	Human-oriented focal length/ speed adaptation
Power Up Action	Auto restore to previous PTZ and lens status after power failure
Idle Motion	Activate Preset/ Scan/ Tour/ Pattern if there is no command in the specified period

General Function

Two-way Talk	Yes
Network Protocol	HTTP; TCP; ARP; RTSP; RTP; UDP; RTCP; SMTP; FTP; DHCP; DNS; DDNS; PPPOE; IPv4/v6; SNMP; QoS; UPnP; NTP
Region of Interest (ROI)	Yes
Edge Storage	FTP; Micro SD card (256G, hot plug)
Interoperability	ONVIF; GB/T28181; CGI; PSIA; Dahua SDK
Browser	IE: IE8 and the later, and explorer with IE core Google: 42 and the earlier Firefox: 42 and the earlier Safari: 10 and the earlier
User/Host	20 channels at most (the total bandwidth 64M)
Security	Authorized username and password; attached MAC address; encrypted HTTPS; IEEE 802.1X; controlled network access
User Management	Support 20 users at most and users are classified as two groups--administrator group and user group.
Malfunction Detection	Network disconnection; IP addresses conflict; SD card error (status or storage space);

General AI Functions

General IVS Analytics	Tripwire/intrusion/auto tracking/human & vehicle classification
-----------------------	---

Professional and Intelligent

Advanced Intelligent Functions	Fire detection & alarm
Cold/Hot Spot Trace	Auto tracking of the hottest spot and the coldest spot in the thermal image

Port

Network	1 10M/100M Ethernet port (RJ-45)
Alarm Input	7 channels
Alarm Output	2 channels

Audio Input	1 channel
Audio Output	1 channel
RS-485	1 channel

Power

Power Supply	36V/2A DC
Power Consumption	Maximum: 80W

Environment

Operating Temperature	-40°C to +70°C (-40°F to 158°F)
Operating Humidity	≤95%
Self-Adaptive	Auto heating to protect the chip under the cold environment

Physical Characteristics

Protection Grade	IP66
Dimensions	520 mm × 269 mm × 390 mm (LxWxH)
Net Weight	≤25kg
Power Adaptor	Contained
Lens	Contained

Certification

Certifications	CE (EN 60950:2000); FCC (FCC Part 15 Subpart B)
----------------	---

Dimensions (mm[inch])

