

DHI-PHSIAO.9-SS

Indoor Fine Pixel Pitch LED



Features:

- · Ultra-thin 25mm and super-light 5.0kg design.
- \cdot 16:9 Goldenaspect rato , can easily achieve pixel to pixel 2K,4K,8K,16K resoluton.
- · CNC die-castng aluminum cabinet, splicing tolerance is controlled within ±0.1mm.
- · All parts support front maintenance.
- · Dot by dot calibraton ensures color richness and brightness uniformity.











Technical Specification

M	od	el
---	----	----

Model	DHI-PHSIA0.9-SS
Parameters	
Pixel Pitch	0.9375mm
Pixel Configuration	4R4G4B
LED Type	IMD 4 in 1
Brightness	600 cd/m ²
Color Temperature	2000K-9500K(adjustable)
Viewing Angle	H160°, V140°
Pixel Density	1,137,778 pixels/m²
Module Size	300mm×168.75mm
Cabinet Size	W600mm×H337.5mm×D25mm
Cabinet Weight	5.0 kg/panel
Area	0.2025m ²
Material	Die-casting Aluminum
Aspect Ratio	16:9

Ingress Protection	Front IP30/Rear IP30
Operating Temperature/ Humidity	-10 °C~+40 °C/10~80%RH
Storage Temperature/ Humidity	-40 C~+60 C/10~80%RH
Dots per Cabinet	640×360 dots
Processing Depth	14 bits
Brightness Control	Manual/Automatic
Contrast Ratio	5000:1
Frame Rate	50/60 Hz
Refresh Rate	3840Hz
Input Voltage	110-240V AC
Input Power Frequency	50~60 Hz
Input Power (max)	450 W/m²
Input Power (typical)	140 W/m²
Lifespan	≥100,000 h

Indoor SS Series | DHI-PHSIA0.9-SS



Installation	Wall Mounted/Floor Mounted/Hanging Type
Maintenance	Front Maintenance
Data Interconnection	CAT5 Cable (L≤100m); multi-mode fiber (L≤500m); single mode fiber (L≤20km)