


DHL460UDM-ES

46" FHD Video Wall Display Unit (Ultra Narrow Bezel 1.7mm)



Technical Specification

Model

Model	DHL460UDM-ES
-------	--------------

Display

Diagonal	46"(16:9)
----------	-----------

LCD Technology	PVA
----------------	-----

Resolution	1920×1080 (FHD)
------------	-----------------

Bezel width	1.15mm(U/L), 0.55mm(R/B)
-------------	--------------------------

Backlight	Direct LED
-----------	------------

Brightness/Luminance	500 cd/m ²
----------------------	-----------------------

Contrast Ratio	4000:1
----------------	--------

Pixel Density	48dpi
---------------	-------

Viewing Angle	H178°, V178°
---------------	--------------

Response time	8ms
---------------	-----

Display Color	8bit(16.7M)
---------------	-------------

Color Temperature	10,000K
-------------------	---------

MTBF	50,000h
------	---------

Signals

Input	CVBS(BNC)×2, VGA(D-Sub)×1, DVI-D×1, HDMI×1, RS232×1, USB×1, IR×1
-------	--

Output	CVBS(BNC)×2, RS232×1
--------	----------------------

Features:

- Industrial level PVA LCD panel, suitable for extensive 24/7 continuous works
- Ultra-narrow 1.7mm bezel-to bezel design(1.15mm bezel on the left and top sides and 0.55mm bezel on the right and bottom sides)
- High contrast ratio and high brightness greatly enhance the video layering, and present the details of the video
- High fidelity digital processing for a brilliant and vivid video
- Built-in 3D COMB filter and 3D noise reduction
- Wide array of connectivity options HDMI, DVI, VGA, BNC, RS232, USB, Audio
- Infrared, RS232 dual mode, supporting remote PC control
- Professional thermal design to extend equipment lifespan
- Built-in power, low energy consumption, ultra-quiet
- Fast stack installation, professional project design, supporting arc-shaped mounting
- Widely used in surveillance center, command center, meeting room, commercial display scenes, etc.



General

Consumption (Standard)	120W	
Consumption (Standby)	≤0.5W	
Power Supply	AC100V~AC240V, 50/60 Hz	
Installation Mode	Floor-standing, wall-mounted	
Control Mode	Infrared, RS232 dual mode, supporting remote PC control	
Gross Weight	28kg(64.6lb)	
Net Weight	22kg(48.4lb)	
Dimension (W×H×D)	1020mm×574.6mm×118.7mm(40.2"×22.6"×4.7")	
Package (W×H×D)	1194mm×810mm×260mm(47"×31.9"×10.2")	
Work Environment	Temperature	0°C~+50°C
	Humidity	20%RH~90%RH

Dimensions(mm)

