

LS650KCH-ES

65" UHD Video Wall Display Unit (Ultra Narrow Bezel 3.5mm)



Technical Specification

Model

Model	LS650KCH-ES
-------	-------------

Display

Diagonal	65"(16:9)
----------	-----------

LCD Technology	PVA
----------------	-----

Resolution	3840x2160 (UHD)
------------	-----------------

Bezel Width	2.3mm (U/L), 1.2mm (R/B)
-------------	--------------------------

Backlight	Direct LED
-----------	------------

Brightness/Luminance	700 cd/m ²
----------------------	-----------------------

Contrast Ratio	4000:1
----------------	--------

Pixel Density	68dpi
---------------	-------

Viewing Angle	H178°, V178°
---------------	--------------

Response Time	8ms
---------------	-----

Display Color	8bit(16.7M)
---------------	-------------

Color Temperature	10,000K
-------------------	---------

MTBF	50,000h
------	---------


Signals

Input	VGA(D-Sub)×1, DVI-D×1, HDMI×2, DP×1, RS232×1, Audio×1, OPS×1, IR×1
-------	--

Output	DP×1, RS232×1, Audio×1
--------	------------------------

Features:

- Industrial level PVA LCD panel, suitable for continuous 24/7 operation
- Ultra-narrow 3.5mm bezel-to bezel design(2.3mm bezel on the left and top sides and 1.2mm bezel on the right and bottom sides)
- High contrast ratio and high brightness greatly enhance the video layering, and present the details of the video
- High fidelity digital processing, brilliant and vivid video
- Built-in 3D COMB filter and 3D noise reduction
- Wide array of connectivity options HDMI, DVI, VGA, DP, RS232, OPS, Audio
- Built-in picture splicing function
- Infrared, RS232 dual mode, supporting remote PC control
- Professional thermal design to extend equipment lifespan
- Built-in power, low energy consumption, ultra-quiet
- Fast stack installation, professional project design, supporting arc-shaped mounting
- Widely used in surveillance center, command center, meeting room, commercial display scenes, etc.



General

Consumption (Standard)	325W	
Consumption (Standby)	≤0.5W	
Power Supply	AC100V ~ AC240V, 50/60 Hz	
Installation Mode	Floor-standing, wall-mounted	
VESA	600×400mm, M6	
Control Mode	Infrared, RS232 dual mode, supporting remote PC control	
Gross Weight	49.5kg(108.9lb)	
Net Weight	42kg(92.4lb)	
Dimension (W×H×D)	1432.6mm×807.6mm×112.6mm(56.4"×31.8"×4.4")	
Package (W×H×D)	1725mm×1045mm×295mm(67.9"×41.2"×11.6")	
Work Environment	Temperature	0 C~+50 C
	Humidity	20%RH~90%RH

Dimensions(mm)

