

LM55-S400

55" UHD LED Monitor



Features:

- · 4K Ultra-HD resolution
- · Using tamper-proof metal housing
- · Suitable for continuous 24/7 operation
- · Slim 8mm narrow bezel design
- · Built-in 3D COMB filter and 3D Noise Reduction
- · 6ms response time for no motion blur, judder or ghosting
- \cdot 1.07B colors, for a realistic and immersive visual experience
- · High fidelity digital processing for a brilliant and vivid video
- · 178°/178° wide uniterupted viewing angle
- · Professional thermal design to extend equipment lifespan
- · Built-in power, low energy consumption, ultra-quiet
- · Support multiple signals, such as HDMI, DP, VGA, USB multimedia, Audio, RS232















Technical Specification

Model	
Model	LM55-S400
Display	
Screen Size	55"
Aspect Ratio	16:9
Resolution	3840×2160 (UHD)
Backlight	LED
Brightness/Luminance	450cd/㎡
Contrast	1000:1
Display Color	1.07B(10bit)
Viewing Angle(H/V)	178°(H)/178°(V)
Response time	6ms
Refresh Rate	60Hz
Signals	
	DP 1.2×1. HDMI 2.0×2. VGA(D-Sub)×1. USB multimedia×1.

_			
Input	DP 1.2×1, HDMI 2.0×2, VGA(D-Sub)×1, USB multimedia×1, Audio×1, RJ45(RS232)×1		
Output	RJ45(RS232)×1		
	Speaker	5W×2	

AC100~240V (+/-10%), 50/60 Hz Power Supply

Consumption (Standard)	<170W	
Consumption (Standby)	≤0.5W	
Туре	Internal	
Net Weight	25.2kg (55.6lb)	
Gross Weight	35kg (77.2lb)	
Bezel Width	8mm (U/L/R/B)	
Wall Mount	400×400mm (15.7"×15.7")	
Dimension without standard (W×H×D)	1227.2×699.6×65.0mm (48.3"×27.5"×2.6")	
Package(W×H×D)	1410×875×255mm (55.5"×34.4"×10.0")	
Work Environment	Temperature	0°C~40°C (32°F~104°F)
work environment	Humidity	10%~85%
Accessory		

HDMI cable, power cable, hanging bracket, remote Standard control Optional Pedestal Certifications

CE/FCC Certifications



Dimensions(mm)



