


# DHI-PHBIA2.5-EH

## Indoor LED Digital Signage



### Features:

- Global ultra-thin design(35mm),over 97% color saturation,exquisite picture quality,low brightness and high gray,8-level freely adjustable brightness.
- Adopt Android system, ver y expandable.
- Support USB、 HDMI Sync、 Lan AAP control to play、 Support WIFI/Ethernet internet connection and so on
- Plug and play,Any video automatically plays full screen,zero setting ,quick and simple.
- User-lever front maintenance , all-weather protection technology, anti-broken LED, moisture-proof, anti-static, radiation-proof, wear-resisting and high-efficiency heat dissipation.



### Technical Specification

#### Model

Model	DHI-PHBIA2.5-EH
-------	-----------------

#### Parameters

Pixel Pitch	2.5mm
Screen Size	83 inch
Module Size (W×H)	300×337.5mm
Module Resolution (W×H)	120×135
Pixel Type	1R1G1B
LED Type	SMD2020
Overall Dimension (W×H×D)	630×2055×42.6mm
Viewing Area (W×H)	600mm×2025 mm
Cabinet Resolution (W×H)	240×810
Cabinet Material	Die-cast Aluminum+Profile
Cabinet Weight	39 kg/cabinet
Pixel Density	160000dots/m <sup>2</sup>
Brightness	0-800cd/m <sup>2</sup> (10 level adjustable)
Grey Level	14 bits

Refresh Rate	3840Hz
Contrast	4000:1
Response Time	≤0.5ms (Typ)
Viewing Angle	160°/160°
Ingress Protection (front/rear)	IP30
Input Voltage	AC100-240V~50/60Hz
Work Temperature	-10 C~+40 C
Work Humidity	10%RH~90%RH
Input Power (max)	600 W/m <sup>2</sup>
Input Power (avg)	200 W/m <sup>2</sup>
Video Interface	HDMIx2 (1 input 1 output), USB 2.0x2
Audio Interface	External Audio interface
Communication Connection	USB/WIFI/RJ45
Installation	Standing (Standard) / Hanging (Optional) / Wall Mounting (Optional) / Movable Installation(Optional)
Maintenance Mode	Front maintenance
Accessories	Tool/Spare parts/HDMI wire/Specification