

DH-IPC-HFW5831E-ZE

8MP WDR IR Bullet Network Camera



- 1/2.5" 8Megapixel progressive scan STARVIS™ CMOS
- H.265&H.264 dual-stream encoding
- 15fps@4K(3840×2160),25/30fps@3Mp(2304×1296)
- Day/Night(ICR), 3DNR, AWB, AGC, BLC
- Multiple network monitoring: Web viewer, CMS(DSS/PSS) & DMSS
- 2.7mm ~12mm motorized lens
- Max. IR LEDs Length 50m
- Micro SD memory, IP67, IK10, PoE



System Overview

With upgraded H.265 encoding technology, Eco-savvy series brings high efficient video compression capability. It can save bandwidth and storage. Meanwhile, the series features starlight, smart IR technology and intelligent image analysis techniques. This series supports reminder function, meanwhile fully protected from dust and water, certified to IP67 and vandal resistant to IK10 standard.

Intelligent Video System (IVS)

IVS is a built-in video analytic algorithm that delivers intelligent functions to monitor a scene for Tripwire violations, intrusion detection, and abandoned or missing objects. A camera with IVS quickly and accurately responds to monitoring events in a specific area. In addition to scene analytics, the camera supports face detection to quickly capture a face and upload the image to a server. The camera also offers tamper detection by recognizing a dramatic scene change and generating a warning message to inspect the camera.

Protection(IP67, IK10, wide voltage)

The camera allows for ±30% input voltage tolerance, suitable for the most unstable conditions for outdoor applications. Its 6KV lightning rating provides effective protection for both the camera and its structure against lightning. Subjected and certified to rigorous dust and immersion tests (IP67) and impact tests (IK10), the camera is the choice for installation in even the most unforgiving environments.

Smart H.265+

Smart H.265+ is the optimized implementation of the H.265 codec that uses a scene-adaptive encoding strategy, dynamic GOP, dynamic ROI, flexible multi-frame reference structure and intelligent noise reduction to deliver high-quality video without straining the network. Smart H.265+ technology reduces bit rate and storage requirements by up to 70% when compared to standard H.265 video compression.

Functions

ePoE technology

The ePoE technology of Dahua, designed internally, adopts advanced 2D-PAM3 coding modulation from physical layer, and realizes full duplex transmission over 800 meters at the speed of 10Mbps, or 300 meters at the speed of 100Mbps via Cat 5 or coaxial cable media. Besides, it supports PoE and PoC power supply technology which has greatly simplified construction and wiring. Dahua ePoE technology offer a new way to accomplish long distance transmission between IP camera and network switch. It allows more flexible surveillance system design, improves reliability and saves construction and wiring cost.

4K technology

4K technology as a revolutionary breakthrough in image, which enhance the expressive image of essence, allowing users to experience the best picture quality brought about by the visual feast. For the purposes of 4K surveillance with four times the 1080P resolution, presented to the user with more details. Under the same scenario by raising the pixels, reduce the camera cost.

Wide Dynamic Range

The camera achieves vivid images, even in the most intense contrast lighting conditions, using industry-leading wide dynamic range (WDR) technology. For applications with both bright and low lighting conditions that change quickly, true WDR (120 dB) optimizes both the bright and dark areas of a scene at the same time to provide usable video.

Technical Specification						
Camera						
Image Sensor		1/2.5” 8Megapixel progressive scan CMOS				
Effective Pixels		3840(H)x2160(V)				
RAM/ROM		512MB/32MB				
Scanning System		Progressive				
Electronic Shutter Speed		Auto/Manual, 1/3~1/100000s				
Minimum Illumination		0.05Lux/F1.4 (Color,1/3s,30IRE) 0.2Lux/F1.4 (Color,1/30s,30IRE) 0Lux/F1.4(IR on)				
S/N Ratio		More than 50dB				
IR Distance		Distance up to 50m (164ft)				
IR On/Off Control		Auto/ Manual				
IR LEDs		4				
Lens						
Lens Type		Motorized/ Auto Iris(DC)				
Mount Type		Board-in				
Focal Length		2.7mm~12mm				
Max. Aperture		F1.4				
Angle of View		H:110°~40° , V:58°~23°				
Optical Zoom		4x				
Focus Control		Motorized				
Close Focus Distance		0.3m				
DORI Distance	Lens	Detect	Observe	Recognize	Identify	
	W	85m(280ft)	34m(112ft)	17m(56ft)	8.5m(28ft)	
	T	228m(748ft)	91m(299ft)	46m(151ft)	23m(75ft)	
Pan/Tilt/Rotation						
Pan/Tilt/Rotation Range		Pan:0°~360°; Tilt:0°~90°; Rotation:0°~360°				
Intelligence						
IVS		Tripwire, Intrusion, Object Abandoned/Missing				
Advanced Intelligent Functions		Face Detection				
Video						
Compression		H.265+/H.265/H.264+/H.264				
Streaming Capability		3 Streams				
Resolution		4K(3840×2160)/ 6M(3072×2048)/5M(3072x1728)/ 5M(2592×1944)/ 4M(2688×1520)/ 3M(2048x1536)/ 3M(2304×1296)/ 1080P(1920×1080)/1.3M(1280x960)/ 720P(1280×720)/ D1(704×576/704×480)/ VGA(640×480)/ CIF(352×288/352×240)				
Frame Rate		Main Stream: 4K(1~15fps)/3M(1~25/30fps)				
		Sub Stream: D1(1~25/30fps)				
		Third Stream: 720P(1~25/30fps)				
Bit Rate Control		CBR/VBR				
Bit Rate		H.264: 24K ~ 10240Kbps H.265: 14K ~ 9984Kbps				

Day/Night		Auto(ICR) / Color / B/W	
BLC Mode		BLC / HLC / WDR	
White Balance		Auto/Natural/Street Lamp/Outdoor/Manual	
Gain Control		Auto/Manual	
Noise Reduction		3D DNR	
Motion Detetion		Off / On (4 Zone, Rectangle)	
Region of Interest		Off / On (4 Zone)	
Electronic Image Stabilization (EIS)		N/A	
Smart IR		Support	
Defog		N/A	
Digital Zoom		16x	
Flip		0°/90°/180°/270°	
Mirror		Off / On	
Privacy Masking		Off / On (4 Area, Rectangle)	
Audio			
Built-in MIC		No	
Network			
Ethernet		RJ-45 (10/100Base-T)	
Protocol		HTTP; HTTPS; TCP; ARP; RTSP; RTP; UDP; SMTP; FTP; DHCP; DNS; DDNS; PPPOE; IPv4/v6; QoS; UPnP;NTP; Bonjour; 802.1x; Multicast; ICMP; IGMP; SNMP	
Interoperability		ONVIF, PSIA, CGI	
Streaming Method		Unicast / Multicast	
Max. User Access		10 Users /20 Users	
Edge Storage		NAS Local PC for instant recording Mirco SD card 128GB	
Web Viewer		IE, Chrome, Firefox, Safari	
Management Software		Smart PSS, DSS, Easy4ip	
Smart Phone		IOS, Android	
Certifications			
Certifications		CE (EN 60950:2000) UL:UL60950-1 FCC: FCC Part 15 Subpart B	
Interface			
Video Interface		N/A	
Audio Interface		NO	
RS485		N/A	
Alarm		2 channel In: 5mA 5VDC 1 channel Out: 300mA 12VDC	
Electrical			
Power Supply		DC12V, PoE (802.3af)(Class 0)	
Power Consumption		<12.95W	

Environmental

Operating Conditions	-30° C ~ +60° C (-22° F ~ +140° F) / Less than 95% RH
Storage Conditions	-30° C ~ +60° C (-22° F ~ +140° F) / Less than 95% RH
Ingress Protection	IP67
Vandal Resistance	IK10

Construction

Casing	Metal
Dimensions	273.2mm×95.0mm×95.0mm (10.76"×3.74"×3.74")
Net Weight	1.11Kg (2.44lb)
Gross Weight	1.51Kg (3.33lb)

Ordering Information

Type	Part Number	Description
8MP camera	DH-IPC-HFW5831EP-ZE	8MP IR Bullet Network Camera, WDR, PAL
	DH-IPC-HFW5831EN-ZE	8MP IR Bullet Network Camera, WDR, NTSC
	IPC-HFW5831EP-ZE	8MP IR Bullet Network Camera, WDR, PAL
	IPC-HFW5831EN-ZE	8MP IR Bullet Network Camera, WDR, NTSC
Accessories (optional)	PFA121	Junction box
	PFA152-E	Pole Mount
	LR1002	ePoE Over Coax Converter

Accessories

Optional:



PFA121
Junction box



PFA152-E
Pole Mount



LR1002
ePoE Over Coax Converter

Junction Mount	Pole Mount
PFA121	PFA121 + PFA152-E

Dimensions (mm/inch)

