

DH-SDBCE4-45-XA

4MP Professional Ultra Smart IP IR PTZ Camera



WizSense

- 1/2.8" 4Megapixel STARVIS™ CMOS
- Powerful 45x optical zoom
- Starlight technology
- Max. 25/30fps@4MP
- Deep-learning-based auto tracking and perimeter protection
- Face detection
- SMD Plus (Smart Motion Detection)
- IR distance up to 250m
- IP67, IK10
- 3th party software support
- Starlight
- Ultra Smart



Launched by Dahua Technology, WizSense is a series of AI products and solutions that adopt independent AI chip and deep learning algorithm. It focuses on human and vehicle with high accuracy, enabling users to fast act on defined targets. Based on Dahua's advanced technologies, WizSense provides intelligent, simple and inclusive products and solutions.

System Overview

Featuring powerful optical zoom and accurate pan/tilt/zoom performance, this camera can provide large monitoring range and great detail. The camera has very excellent low light performance due to adopting the latest starlight technology. The camera is equipped with smooth control, high quality image and good protection, which make it can meet most of the requirements of video surveillance applications.

Functions

Starlight Technology

For challenging low-light applications, Dahua's Starlight Ultra-low Light Technology offers best-in-class light sensitivity, capturing color details in low light down to 0.005lux. The camera uses a set of optical features to balance light throughout the scene, resulting in clear images in dark environments.

Wide Dynamic Range

The camera achieves vivid images, even in the most intense contrast lighting conditions, using industry-leading wide dynamic range (WDR) technology. For applications with both bright and low lighting conditions that change quickly, True WDR (120 dB) optimizes both the bright and dark areas of a scene at the same time to provide usable video.

Auto-tracking

This feature controls the pan/tilt/zoom actions of the camera to automatically track an object in motion and to keep it in the scene. The tracking action can be triggered manually or automatically by defined rules. Once a rule is triggered, the camera can zoom in and track the defined target automatically.

Perimeter Protection

Automatically filtering out false alarms caused by animals, rustling leaves, bright lights, etc. Enables system to act secondary recognition for the targets. Improving alarm accuracy.

Environmental

Dahua cameras operate in extreme temperature environments, rated for use in temperatures from -40°C ~ 70°C (-40°F ~ +158°F) with 95% humidity. The camera complies with the IK10 Vandal Resistance impact rating. Subjected to rigorous dust and water immersion tests and certified to the IP67 Ingress Protection rating makes it suitable for demanding outdoor applications.

Protection

The camera allows for ±25% input voltage tolerance, suitable for the unstable conditions for outdoor applications. Its 8KV lightning rating provides effective protection for both the camera and its structure against lightning.

Interoperability

The camera conforms to the ONVIF (Open Network Video Interface Forum) specifications, ensuring interoperability between network video products regardless of manufacturer.

SMD Plus

With Deep-Learning Algorithm, Dahua SMD Plus filters the motion detection alarm triggered by non-concerned target and recognizes human and vehicle effectively, sending alarms when human and vehicle intrude.

Technical Specification

Camera	
Image Sensor	1/2.8" STARVIS™ CMOS
Pixels	4 MP
Max. Resolution	2560 (H) × 1440 (V)
Scanning System	Progressive
Electronic Shutter Speed	1/1 s–1/30,000 s
Minimum Illumination	Color: 0.005 Lux@F1.6; B/W: 0.0005 Lux@F1.6; 0 Lux@F1.6 (IR on)
Illumination Distance	Distance up to 250 m (820 ft)
Illumination On/Off Control	Auto/Manual
Illuminator Number	6
Interoperability	SDK & API support
Max. User Access	10 Users / Unlimited(Up to 64Mbps)

Lens

Focal Length	3.95 mm–177.75 mm
Max. Aperture	F1.6–F4.95
Angle of View	H: 70.3°–1.8°; V: 37°–1°; D: 69.3°–2°
Optical Zoom	45x
Focus Control	Auto/Manual
Iris Control	Auto/Manual
Close Focus Distance	10 mm–3,000 mm

DORI Distance

DORI Distance	Detect	Observe	Recognize	Identify
	3176 m (10420 ft)	1271 m (4170 ft)	635 m (2083 ft)	318 m (1043 ft)

PTZ

Pan/Tilt Range	Pan: 0°–360° endless; Tilt: -20°–90°, auto flip 180°
Manual Control Speed	Pan: 0.1°–260° /s; Tilt: 0.1°–120° /s
Preset Speed	Pan: 300° /s; Tilt: 200° /s
Presets	300
Tour	8 (up to 32 presets per tour)
Pattern	5
Pan	5
Power up Action	Auto restore to previous PTZ and lens status after power failure
Idle Motion	Activate Preset/ Scan/ Tour/ Pattern if there is no command in the specified period
Protocol	DH-SD, Pelco-P/D (Auto recognition)

Artificial Intelligence

Perimeter Protection	Tripwire, Intrusion. Support alarm triggering by target types(human and vehicle) Filtering out false alarms caused by animals, rustling leaves, bright lights, etc
Auto Tracking	Support

Video Structuralization	Support human, motor vehicle and non-motor vehicle image capture
SMD Plus	Support
Face Detection	Support

General Intelligence

Event Trigger	Motion detection, Video tampering , Scene changing, Network disconnection, IP address conflict, Illegal Access, Storage anomaly
General Intelligence	Object Abandoned/Missing

Video

Compression	H.265+/H.265/H.264+/H.264/MJPEG(Sub Stream)
Streaming Capability	3 Streams
Resolution	4M (2560 × 1440)/3M (2048 × 1536)/1080p (1920 × 1080)/720p (1280 × 720)/D1 (704 × 576/704 × 480)/CIF (352 × 288/352 × 240)
Frame Rate	Main stream: 4M/3M (1–25/30 fps), 1080p/1.3M/720p (1–25/30 fps)
	Sub stream1: D1/CIF (1–25/30 fps)
	Sub stream2: 1080p (1–25/30 fps), 720p (1–25/30 fps)
Bit Rate Control	CBR/VBR
Bit Rate	H.265/H.264: 3 Kbps–20,480 Kbps
Day/Night	Auto (ICR) / Color / B/W
BLC	Support
WDR	120 dB
HLC	Support
White Balance	Auto, ATW, Indoor, Outdoor, Manual
Gain Control	Auto / Manual
Noise Reduction	Ultra DNR (2D/3D)
Motion Detection	Support
Region of Interest	Support
Image Stabilization	Electronic
Defog	Support
Digital Zoom	16x
Flip	180°
Privacy Masking	Up to 24 areas

Audio

Compression	G.711a/G.711Mu/AAC/G.722 / G.726/G.729/MPEG2-L2
-------------	---

Network

Ethernet	RJ-45 (10Base-T/100Base-TX)
Protocol	IPv4/IPv6, HTTP, HTTPS, SSL, TCP/IP, UDP, UPnP, ICMP, IGMP, SNMPv1/v2c/v3(MIB-2), ARP, RTCP, RTSP, RTMP, RTP, SMTP, NTP, DHCP, DNS,PPPOE,DDNS,FTP, IP Filter,QoS,Bonjour,802.1x
Interoperability	ONVIF Profile S&G&T, API
Streaming Method	Unicast / Multicast

User/Host	20 users
Storage	NAS (Network Attached Storage), Local PC for instant recording, Micro SD card 256GB
Browser	IE, Chrome, Firefox, Safari
Management Software	Smart PSS, DSS, DMSS
Smart Phone	IOS, Android

Certifications

Certifications	CE: EN55032/EN55024/EN50130-4 FCC: Part15 subpartB, ANSI C63.4- 2014
----------------	---

Port

RS485	1
Audio I/O	1 (Line in; bare wire)/1 (Line out; bare wire)
Alarm I/O	7/2

Power

Power Supply	DC 24 V/2.5 A \pm 25%; PoE+(802.3at)
Power Consumption	13 W, 26 W (IR On, Heater On)

Environment

Operating Conditions	-40 °C to 70 °C (-40 °F to +158°F) / Less than 95% RH
Protection	IP67, IK10

Structure

Casing	Aluminum alloy
Dimensions	$\phi 209 \times 337.4$ mm
Net Weight	5.9 kg (13 lb)
Gross Weight	9.6 kg (21.16 lb)

Ordering Information

Type	Part Number	Description
4MP WizSense PTZ Camera	DH-SDBCE4-45-XA	4MP Professional Ultra Smart IP IR PTZ Camera, WDR, PAL
	DH-SDBCE4-45-XA	4MP Professional Ultra Smart IP IR PTZ Camera, WDR, NTSC
	DH-SDBCE4-45-XA	4MP Professional Ultra Smart IP IR PTZ Camera, WDR, PAL
	DH-SDBCE4-45-XA	4MP Professional Ultra Smart IP IR PTZ Camera, WDR, NTSC
Accessories	PFB305W	Wall Mount Bracket
	DC 24 V/2.5 A	Power Adapter
	PFA111	Mount Adapter
	PFA140	Power Box
	PFB300C	Ceiling Mount Bracket
	PFA120	Junction Box
	PFA150	Pole Mount Bracket
	PFA151	Corner Mount Bracket
	PFB303S	Parapet Mount Bracket

Accessories

Included:



PFB305W
Wall Mount Bracket



DC 24 V/2.5 A
Power Adapter

Optional:



PFA111
Mount Adapter



PFA140
Power Box




PFB300C
Ceiling Mount Bracket



PFA120
Junction Box









PFA150
Pole Mount Bracket



PFA151
Corner Mount Bracket



PFB303S
Parapet Mount Bracket

Ceiling Mount PFA111 + PFB300C 	Junction Mount PFB305W 
Power Box Mount PFB305W + PFA140 	Pole Mount PFB305W + PFA150 
Corner Mount PFB305W + PFA151 	Parapet Mount PFA111+ PFB303S 

Dimensions (mm[inch])

