


# DHI-PHEIA4-TH

## Indoor Fine Pixel Pitch LED



### Features :

- Three-in-one integrated design of control board.
- Support Front/Rear maintenance.
- Tool free disassembly of Hub board.
- Hardwired wireless design.
- Support GOB encapsulation technology (customizable)
- Dot by dot calibration ensures color richness and brightness uniformity.



### Technical Specification

#### Model

Model	DHI-PHEIA4-TH
-------	---------------

#### Parameters

Pixel Pitch	4.0mm
Pixel Configuration	1R1G1B
LED Type	SMD2121
Brightness (Max)	600 nit
Color Temperature	2000K-9500K
Viewing Angle	H140° / V140°
Pixel Density	62,500 dots/m <sup>2</sup>
Module Size	320mm×160mm
Module Resolution	80x40 dots
Cabinet Size	W640mm×H480mm×D54mm
Cabinet Resolution (W×H)	160×120 dots
Cabinet Weight	6.5 kg ± 0.1
Cabinet Material	Die-casting Aluminum

Operating Temperature/ Humidity	-10 C~+45 C/10~80%RH
Storage Temperature/ Humidity	-20 C~+55 C/10~80%RH
IP Rating	Front IP30/Rear IP30
Aspect Ratio	4:3
Gray Scale	12-14 bit
Contrast Ratio	5000:1
Refresh Rate	3840Hz
Input Voltage	AC 100~220V (+/-10%)
Input Power (max)	650 W/m <sup>2</sup>
Input Power (Avg)	210 W/m <sup>2</sup>
Installation	Wall Mounted/Floor Mounted
Maintenance	Front/Rear Maintenance
Lamp Lifespan	≥100,000 H
Signal Transmission Distance	CAT5 Cable ( L≤100m ), multi-mode fiber ( L≤300m ), single mode fiber ( L≤10km)