

# DH-SDT4E425-4F-GB-A-PV1

X-Spans 4MP+4MP 25x TiOC WizSense Network PTZ Camera



**Wiz Sense**

Launched by Dahua Technology, WizSense is a series of AI products and solutions that adopt independent AI chip and deep learning algorithm. It focuses on human and vehicle with high accuracy, enabling users to fast act on defined targets. Based on Dahua's advanced technologies, WizSense provides intelligent, simple and inclusive products and solutions.

## System Overview

Designed with more lens than the conventional PTZ camera, the X-Spans series camera captures an expansive view, producing wide, vivid images. It has the combined power of the panoramic and detail camera in its structure and is highly cost-effective, greatly reducing the installation cost of security systems. It also leverages its two cameras to perform smart tracking, and has an independent mode that allows you to separately use each camera.

## Functions

### Starlight Technology

For challenging low-light conditions, Dahua's Starlight Ultra-low Light Technology offers the best in light sensitivity, capturing color in vivid detail, even in lighting as low as 0.005 lux. The camera uses a set of optical features to balance light throughout the scene, producing clear images in dark environments.

### Smart Tracking

The panoramic camera links with the detail camera to track targets. When the target enters the panoramic area, the detail camera starts to monitor them and tracks their movement by rotating, zooming and focusing the PTZ camera lens. This allows the camera to produce highly detailed images with the movement of targets for security personnel. 3D Target Positioning, Image Freezing and PTZ Status Display.

- Panorama: 1/2.8" 4 Megapixel Full Color F1.0 CMOS.
- Detail: 1/2.8" 4 Megapixel STARVIS™ CMOS.
- 25x optical zoom.
- Max. 25/30fps@4M.
- IR distance up to 100 m.
- Auto tracking 3.0.
- Face Detection.
- Perimeter protection.
- Active deterrence.
- Smart dual light +.



### Smart H.265+ & Smart H.264+

With advanced scene-adaptive rate control algorithm, Dahua smart encoding technology realizes the higher encoding efficiency than H.265 and H.264, provides high-quality video, and reduces the cost of storage and transmission.

### Perimeter Protection

Automatically filters out false alarms caused by animals, rustling leaves, bright lights, and more, and uses secondary recognition during target detection to improve alarm accuracy.

### Protection (IP66, TVS 6000 V)

IP66, TVS 6000 V lightning proof, surge protection, and voltage transient protection.

### Smart Dual Light +

Both the panoramic camera and detail camera support smart dual light. In intelligent illumination mode, the channels of both cameras can switch together from one type of image to another. When a target enters the panoramic area, both channels switch from displaying black and white images to color images at the same time. After the target leaves, they both simultaneously switch back to black and white.

Technical Specification				
Camera				
Image Sensor	Panorama: 1/2.8" CMOS; Detail: 1/2.8" CMOS			
Pixel	Panorama: 4 MP; Detail: 4 MP			
Max. Resolution	Panorama: 2560 (H) × 1440 (V); Detail: 2560 (H) × 1440 (V)			
ROM	Panorama: 4 GB; Detail: 4 GB			
RAM	Panorama: 1 GB; Detail: 1 GB			
Electronic Shutter Speed	Panorama: 1/3s-1/100000s; Detail: 1s-1/30000s			
Scanning System	Progressive			
Slow Shutter	Yes			
Min. Illumination	Panorama: 0.0005 lux@F1.0 (Color, 30 IRE); 0.0005 lux@F1.0 (B/W, 30 IRE); 0 lux (illuminator on); Detail: 0.005 lux@F1.6 (Color, 30 IRE); 0.0005 lux@F1.6 (B/W, 30 IRE); 0 lux (illuminator on)			
Illumination Distance	Panorama: 30 m (98.43 ft) (IR); 30 m (98.43 ft) (white light); Detail: 100 m (328.08 ft) (IR) 50 m (164.04 ft) (white light)			
Illuminator On/Off Control	Panorama: Auto; Manual; Off; Detail: Zoom Prio; Auto; Manual; Off			
Illuminator Number	Panorama: 2 (IR); 2 (white light); Detail: 2 (IR); 2 (dual light Fusion)			
Lens				
Focal Length	Panorama: 2.8 mm; Detail: 4.8 mm–125 mm			
Max. Aperture	Panorama: F1.0; Detail: F1.6–F3.6			
Field of View	Panorama: H: 101°; V: 53°; D: 120°; Detail: H: 51.9°–3.0°; V: 39.7°–2.2°; D: 63.1°–3.7°			
Optical Zoom	Panorama: NA; Detail: 25×			
Focus Control	Auto; semi-auto; manual			
Close Focus Distance	Panorama: 0.2 m (0.66 ft); Detail: 0.1 m–0.5 m (0.33 ft–1.64 ft)			
Iris Control	Auto; manual			
DORI Distance	Detect	Observe	Recognize	Identify
	2500 m (8202.10 ft)	987.5 m (3239.83 ft)	500 m (1640.42 ft)	250 m (820.21 ft)
PTZ				
Pan/Tilt Range	Panorama camera: Tilt: 13° to 23°; Detail: Pan: 0° to 360° endless; Tilt: –15° to 90°, auto flip 180°			
Manual Control Speed	Pan: 0.1°/s–200°/s; Tilt: 0.1°/s–120°/s			
Preset Speed	Pan: 240°/s; Tilt: 200°/s			
Zoom Speed	approx. 2.2 s			
Preset	300			
Tour	8 (up to 32 presets per tour)			
Pattern	5			
Scan	5			
Power-off Memory	Yes			
Idle Motion	Pattern; Preset; Scan; Tour			
Intelligence				
IVS (Perimeter Protection)	Tripwire; intrusion; climbing fences; loitering detection; region entrance detection, region exiting detection, missing object; fast moving; parking detection; people gathering; vehicle/human alarm classification; linking the detail camera to SMD4.0			
Auto Tracking & Quick Pick	Yes			
Park Action & Scheduled Task	preset, pattern scan, tour scan, auto scan, tilt scan, random scan, frame scan, panorama scan			
Active Deterrence				
Light Warning	Red-blue light warning Flash duration: 5 s–30 s Flash frequency: high, medium, low			
Sound Warning	Offers 11 sound alarms and supports importing Custom sound alarms.			
Video				
Video Compression	H.265; H.264B; H.264; H.264H; MJPEG(Sub Stream 1); smart H.265+; smart H.264+			
Streaming Capability	3 streams			
Resolution	Panorama: 4M (2560 × 1440); 3M (2048 × 1536); 3M (2304 × 1296); 1080P (1920 × 1080); 1.3M (1280 × 960); 720P (1280 × 720); D1 (704 × 576/704 × 480); VGA (640 × 480); CIF (352 × 288/352 × 240) Detail: 4M (2560 × 1440); 3M (2048 × 1536); 3M (2304 × 1296); 1080P (1920 × 1080); 1.3M (1280 × 960); 720P (1280 × 720); D1 (704 × 576/704 × 480); VGA (640 × 480); CIF (352 × 288/352 × 240)			
Video Frame Rate	Main stream: 4 MP/3 MP/1080p/1.3 MP/720p@ (1–25/30 fps) Sub stream 1: D1/CIF/VGA@(1–25/30 fps) Sub stream 2: 1080p/1.3 MP/720p@(1–25/30 fps)			
Bit Rate Control	CBR/VBR			
Video Bit Rate	H264: 96 Kbps–14848 Kbps H265: 38 Kbps–8960 Kbps			
Day/Night	Auto (ICR)/Color/B/W, Scheduled-Switch.			
BLC	Yes			
WDR	120 dB			
HLC	Yes			
White Balance	Auto; indoor; outdoor; ATW; manual; sodium lamp; fluorescent lamp; natural light; locked White Balance			
Gain Control	Auto; manual			
Noise Reduction	2D NR; 3D NR			
SVC	YES			
Region of Interest (RoI)	Fixed 8 Area, (Dynamic Target Tracking, Main Stream, Sub-Stream and Third Stream)			
Image Stabilization	EIS			
Defog & Demist	Electronic & Demist by heating the glass for lens inside.			
Digital Zoom	16×			

Image Rotation	180°
S/N Ratio	≥ 52 dB
Regional Focus	Yes
Regional Exposure	Yes
Image Parameters Switch	Yes

### Audio

Audio Compression	PCM; G.711alaw; G.711Mu; G.726; MPEG2-Layer2; G722.1;G729; G723; MP2L2, AAC
Audio Bit rate	32 kbps, 40 kbps, 48 kbps, 56 kbps, 64 kbps, 80 kbps, 96kbps, 112 kbps, 128kbps, 144 kbps, 160 kbps, 192 kbps
Audio Sampling Rate	16 kHz, 32 kHz, 48 kHz, PCM: 8 kHz, 16 kHz, 32 kHz, 48kHz
Environment Noise Filtering	Yes

### Certification

Certifications	UL; CE: EN55032/EN55024/EN50130-4 FCC: Part15 subpartB, ANSI C63.4-2014
----------------	--

### Network

Network Port	RJ-45 (10/100 Base-T)
Network Protocol	FTP; RTMP; IPV6; Bonjour; IPv4; DNS; RTP; PPPoE; NTP; RTP; 802.1x; HTTPS; SNMP; TCP/IP; DDNS; UPnP; NFS; ICMP; UDP; IGMP; HTTP; SSL; DHCP; SMTP; Qos; RTSP; ARP
Interoperability	ONVIF(Profile S&G&T);CGI;SDK Auto Register.
Streaming Method	Unicast/Multicast
Simultaneous Live View	20
User/Host	32 (total bandwidth: 128 M)
Storage	FTP; Micro SD card (up to 512 G); NAS (NFS, SMB/CIFS), ANR with Video Content Analytics.
Browser	IE 10+ and later versions Chrome 57 and later versions Firefox 52 and later versions iOS 10 and later versions
Cyber Security	Video encryption; firmware encryption; configuration encryption; Digest; WSSE; account lockout; security logs; IP/MAC filtering; generation and importing of X.509 certification; syslog; HTTPS; 802.1x; trusted boot trusted execution; trusted upgrade, HTTPS encryption.
Management Software	DMSS; DSS Pro
Mobile Client	iOS; Android

### Port

Audio Input	1 channel (LINE IN, bare wire)
Audio Output	1 channel (LINE OUT, bare wire)
Alarm Input	2 (on-off value input: 0–5 VDC)
Alarm Output	1
Alarm Linkage	Capture; recording; send email; preset; tour; pattern; alarm digital input; audio; warning light
Alarm Event	Motion/tampering detection; audio detection; network disconnection detection; IP conflict detection; memory card state detection; memory space detection

### Power

Power Supply	12 VDC, 3 A ± 10%; PoE+ (802.3at)
Power Consumption	Basic: 12 W Max. (Basic power consumption + illuminator+sound and light warning +PTZ operation + Heater ): 25 W (12 VDC)

### Environment

Operating Temperature	–40 °C to +65 °C (–40 °F to +149 °F)
Operating Humidity	≤ 95%
Protection	Protection TVS 6000 V lightning proof;IP66; surge protection;

### Structure

Product Dimensions	160.0 mm × 184.4 mm × 304.6 mm (6.30" × 7.26" × 11.99")(L × W × H)
Net Weight	3.41 kg (7.52 lb)

### Ordering Information

Type	Model	Description
4MP 25X TIOC WizSense Network PTZ Camera	DH-SDT4E425-4F-GB-A-PV1	X-Spans 4MP+4MP 25x TIOC WizSense Network PTZ Camera
	SDT4E425-4F-GB-A-PV1	X-Spans 4MP+4MP 25x TIOC WizSense Network PTZ Camera
Accessories	PFB305W	Wall Mount Bracket
	DC12V/3A	Power Adapter
	PFA126	Mount Adapter
	PFA111	Mount Adapter
	PFB300C	Ceiling Mount Bracket
	PFB301C	Ceiling Mount Bracket
	PFA151	Corner Mount Bracket
	PFA150	Pole Mount Bracket
	PFB303S	Parapet Mount Bracket
	PFB301S-E	Plane Mount Bracket

**Accessories**

Included:



PFB305W  
Wall Mount  
Bracket

Optional:



DC12V/3A  
Power Adapter



PFA126  
Mount Adapter



PFA111  
Mount Adapter



PFB300C  
Ceiling Mount  
Bracket



PFB301C  
Ceiling Mount Bracket



PFA151  
Corner Mount Bracket



PFA150  
Pole Mount Bracket



PFB303S  
Parapet Mount Bracket



PFB301S-E  
Plane Mount Bracket

Wall Mount PFB305W+PFA126	Ceiling Mount 1 PFA111+PFB300C	Ceiling Mount 2 PFA111+PFB301C
Pole Mount (Vertical) PFB305W+PFA150	Corner Mount PFB305W+PFA151	Pole Mount (Horizontal) PFA111+PFB300C+PFA150
Plane Mount PFB301S-E	Parapet Mount PFA111+PFB303S	

**Dimensions (mm[inch])**

