

## DHI-PHSIAO.9-SS

Indoor Fine Pixel Pitch LED



## **Features:**

- · Ultra-thin 25mm and super-light 5.0kg design.
- $\cdot$  16:9 Golden aspect ratio , can easily achieve pixel to pixel 2K,4K,8K,16K resoluton.
- · CNC die-casting aluminum cabinet, splicing tolerance is controlled within ±0.1mm.
- · Supports dual backup of power supply and signals (customizable).
- · Dot by dot calibraton ensures color richness and brightness uniformity.













## **Technical Specification**

M	ode
---	-----

Model	DHI-PHSIAO.9-SS	
Parameters		
Pixel Pitch	0.9375mm	
Pixel Configuration	1R1G1B	
LED Type	IMD 4IN1	
Brightness (Max)	600 nit	
Color Temperature	2000k ~ 9500K(adjustable)	
Viewing Angle	H160°/V140°	
Pixel Density	1137,778dots/m²	
Module Size	300mm×168.75mm	
Module Resolution	320x180 dots	
Cabinet Size	W600mm×H337.5mm×D25mm	
Cabinet Resolution (W×H)	480×270 dots	
Cabinet Weight	4.5 kg ± 0.5	
Cabinet Material	Die-cast Aluminum	

Operating Temperature/ Humidity	-20 °C~+50 °C/10~80%RH
Storage Temperature/ Humidity	-25 °C~+60 °C/10~80%RH
IP Rating	Front IP30/Rear IP30
Aspect Ratio	16:9
Gray Scale	14 bits
Contrast Ratio	5000:1
Refresh Rate	3840Hz
Input Voltage	AC 110~220V (+/-10%)
Input Power (max)	470 W/m <sup>2</sup>
Input Power (Avg)	160 W/m <sup>2</sup>
Installation	Wall Mounted/Floor Mounted
Maintenance	Front Maintenance
Lamp Lifespan	≥100,000 H
Signal Transmission Distance	CAT5 Cable ( L $\leq$ 100m ), multi-mode fiber ( L $\leq$ 300m ), single mode fiber (L $\leq$ 10km)



## **Dimensions**





