

## DHI-PHSIA1.5-LS Indoor Fine Pixel Pitch LED





## Features :

- · Light and Ultra-thin, 45mm cabinet thickness.
- · Quickly adjusting the flatness of the back without disassembling the screen.
- Magnetic front maintenance module for quick disassembly

· Optional installation methods including wall mount, arc mount and floor-standing mount.



## **Technical Specification** Model DHI-PHSIA1.5-LS Model Operating Temperature/ -10 C~+45 C/10~80%RH Parameters Humidity Storage Temperature/ Pixel Pitch 1 5625mm -25 °C~+60 °C/10~80%RH Humidity Pixel Configuration 1R1G1B Front IP30 / Rear IP30 IP Rating LED Type SMD 1212 Aspect Ratio 16:9 Brightness (Max) 800 nit 14 bits Gray Scale Color Temperature 4000k ~ 9500K(adjustable) Contrast Ratio 3000:1 H140°/V130° Refresh Rate 3840Hz Viewing Angle AC 110~220V (+/-10%) Pixel Density 409,600 dots/m<sup>2</sup> Input Voltage Input Power (max) 500 W/m<sup>2</sup> Module Size 300mm×168.75mm 200 W/m<sup>2</sup> Module Resolution Input Power (Avg) 192x108 dots W600mm×H337.5mm×D45mm Installation Wall Mounted/Floor Mounted Cabinet Size Maintenance Front Maintenance Cabinet Resolution (W×H) 384×216 dots ≥100,000 H Lamp Lifespan Cabinet Weight 5.76 kg±0.5 CAT5 Cable ( L≤100m ), multi-mode fiber ( L≤300m ), Cabinet Material Die-cast Aluminum Signal Transmission Distance single mode fiber (L≤10km)

Rev 002.000 © 2022 Dahua. All rights reserved. Design and specifications are subject to change without notice. The images, specifications and information mentioned in the document are only for reference, and might differ from the actual product.



## Dimensions



Rev 002.000 © 2022 Dahua. All rights reserved. Design and specifications are subject to change without notice. The images, specifications and information mentioned in the document are only for reference, and might differ from the actual product.