

DHI-PHSIA1.8-SS

Indoor Fine Pixel Pitch LED



Features:

- · Ultra-thin 25mm and super-light 5.0kg design.
- \cdot 16:9 Golden aspect ratio , can easily achieve pixel to pixel 2K,4K,8K,16K resoluton.
- · CNC die-casting aluminum cabinet, splicing tolerance is controlled within ±0.1mm.
- · Supports dual backup of power supply and signals (customizable).
- · Dot by dot calibraton ensures color richness and brightness uniformity.













Technical Specification

M	ode
---	-----

Model	DHI-PHSIA1.8-SS
Parameters	
Pixel Pitch	1.875mm
Pixel Configuration	1R1G1B
LED Type	SMD1515
Brightness (Max)	600 nit
Color Temperature	2000k ~ 9500K(adjustable)
Viewing Angle	H160°/V140°
Pixel Density	284,444 dots/m²
Module Size	300mm×168.75mm
Module Resolution	160x90 dots
Cabinet Size	W600mm×H337.5mm×D25mm
Cabinet Resolution (W×H)	320×180 dots
Cabinet Weight	4.5 kg ± 0.5
Cabinet Material	Die-cast Aluminum

Operating Temperature/ Humidity	-20 °C~+50 °C/10~80%RH
Storage Temperature/ Humidity	-25 °C~+60 °C/10~80%RH
IP Rating	Front IP30 / Rear IP30
Aspect Ratio	16:9
Gray Scale	14 bits
Contrast Ratio	5000:1
Refresh Rate	3840Hz
Input Voltage	AC 110~220V (+/-10%)
Input Power (max)	400 W/m ²
Input Power (Avg)	135 W/m²
Installation	Wall Mounted/Floor Mounted
Maintenance	Front Maintenance
Lamp Lifespan	≥100,000 H
Signal Transmission Distance	CAT5 Cable (L≤100m), multi-mode fiber (L≤300m), single mode fiber (L≤10km)



Dimensions





