


# DHI-PHROA2.97-MH

## General Outdoor Rental LED



### Features :

- 500x500mm and 500x1000mm cabinet size design, support splicing installation with up and down.
- Front IP65/Rear IP65 protection grade, achieve stable outdoor performance.
- Radian lock, support installed with internal and external radian, Radians support  $0^\circ$ ,  $\pm 3^\circ$ ,  $\pm 6^\circ$ .
- Good grey scale even at low brightness, brings profound levels and abundant colors.
- Customized A8s receiving card.



### Technical Specification

#### Model

Model	DHI-PHROA2.97-MH
-------	------------------

#### Parameters

Pixel Pitch	2.976mm
Pixel Type	1R1G1B
LED Type	SMD1515
Brightness(MAX)	4500 nit
Color Temperature	6500K-8000K (adjustable)
Viewing Angle (H/V°)	140°/120°
Pixel Density	112,896 dots/m <sup>2</sup>
Module Size (W×H)	250x250mm
Module Resolution (W×H)	84x84dots
Cabinet Size (W×H×D)	500x500x75mm
Cabinet Resolution (W×H)	168x168
Cabinet Weight	9kg±0.1
Cabinet Material	Die-cast aluminum

Cabinet Aspect Ratio	1:1
IP Rating	Front IP65/Rear IP65
Operating Temperature/Humidity	-20 C ~+50 C /10%~80%RH
Storage Temperature/Humidity	-40 C ~+60 C /10%~90%RH
Gray Scale	14 bits
Contrast Ratio	10000:1
Refresh Rate	3840 Hz
Input power frequency	50-60 Hz
Input Voltage	AC110~220V (+/-10%)
Input Power (Max)	700W/m <sup>2</sup>
Input Power (Avg)	210W/m <sup>2</sup>
Installation Mode	Floor Mounted/Hanging
Maintenance Mode	Rear
Signal Transmission Distance	CAT5 Cable ( L≤100m ), multi-mode fiber ( L≤300m ), single mode fiber ( L≤10km)